



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

SPECIFICATIONS
 Rated Current:3.0AMP
 Contact Resistance:20m Ω Max
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000M Ω Min
 Operation Temperature:-40 $^{\circ}$ c to +105 $^{\circ}$ c

Contact Material:Copper Alloy
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 260 $^{\circ}$ C $\pm 5^{\circ}$ C 5S

Ordering Information

PM 254 - * - N - Z - * - **

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 2-40Pin	Type Z=直针 S=弯针 R=弯脚	Length (Plastic) (mm)	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin
--	-----------------------	------------------------------	--------------------------	--

			GENERAL TOLERANCE		制图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD				
			DIM	TOL	审核 CHECK						
			X.X	± 0.30	批准 APPROVAL	产品名称 TITLE		2.54双排 排母 直针(塑高8.5)	版本 REV.	A	
1			初版发行			比例 SCALE	产品料号 PART NO.		PM254-2-N-Z-8.5-XX(L11.7)	单位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	$\pm 3.0^{\circ}$	投影 Projection	材料 MATERIAL		页次 SHEET	1/1		