



P.C.B LAYOUT

材质
 塑胶 :PA6T+30%(UL94V-0)黑色
 端子 :磷铜
 接触电镀: 镍底、表面镀金
 电镀颜色: 黄色

产品规范
 额定电流: 1Amp
 工作温度: -40°C to +105°C
 接触电阻: 20mΩ MAX
 绝缘电阻: 1000MΩ MIN
 耐电压值: 500V AC
 PIN数 : 6~100P

MODEL: F1.27S-4.3×3.0E-2×nP		DRAWN BY : <i>Lei qin</i>		DATE:		GENERAL TOLERANCE: (UNLESS SPECIFIED)	
TITLE : 1.27间距4.3高贴片带柱排母		CHECKED BY : <i>Liwei</i>		DATE:			
DRAWING NO:		REV. : A		APPROVED BY: <i>Wuxin</i>		X. ±0.30mm X.* ± 3'	
SHEET: 1 OF 1		SCALE: 3:1		SIZE: A4		X.X ±0.25mm X.X* ± 2'	
				UNIT : mm		X.XX ±0.20mm X.XX* ± 1'	
						X.XXX±0.10mm X.XXX* ± 0.5'	


深圳市吉威电子有限公司
SZJUSTWELL ELECTRONICS CO., LTD

MEASURE POINT:
 QUADRANT POINT (QP)
 TANGENCY POINT (TP)
 INTERSECTION POINT (IP)

NO:	PARTICULAR	BY	DATE
REVISIONS			