

Datasheet revision 1.5 www.chipquik.com

# Liquid Flux Water Washable in 30ml (1.0oz) Squeeze Bottle w/tip

# **Product Highlights**

A liquid flux that is non-flammable
Low solids
Water soluble
Highly Activated Organic Acid (OA)
VOC Free
Ideal for all rework, solder, and de-solder applications
Excellent wetting
Easily cleaned with water or isopropyl alcohol (IPA)
Can be used with Leaded and Lead-Free applications



## **Specifications**

Flux Type: Water Washable Liquid Flux (for Leaded and Lead-Free applications)
Flux Classification: ORM1 (Water Soluble, Must be cleaned off post-use using Water or IPA)

VOC Content: VOC Free Specific Gravity: 1.09

**RoHS 3 and REACH compliant** 

Packaging: 30ml Squeeze Bottle

Shelf Life: Refrigerated >24 months, Unrefrigerated >24 months

#### Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

# **Transportation**

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Yes

Yes

### **Cleaning**

This is a water soluble liquid flux, post-use cleaning is required. Clean with water or isopropyl alcohol (IPA).

## **Conforms to the following Industry Standards:**

J-STD-004B, Amendment 1 (Solder Fluxes): RoHS 3 Directive 2015/863/EU:

1