

# **DATA SHEET**

# **ALUMINUM HOUSED RESISTORS**

High Power, Wirewound Chassis Mount AHA series AHP series

5W to 50W RoHS compliant & Halogen Free



**YAGEO** 





#### **APPLICATIONS**

- Power, pulse application
- Industry electronic
- **BMS**
- Large-sized machinery

#### **FEATURES**

- Reduced size
- Heatsink mounted
- Excellent surge performance
- Corrosion-resistant aluminum are corrugated for added strength and power dissipation
- RoHS compliant & halogen-free

#### ORDERING INFORMATION

Part number of the aluminum housed power wirewound resistor resistors are identified by the series, power rating, tolerance, packing, temperature coefficient, type and resistance value.

#### **PART NUMBER**

<u>AHA</u>	<u>500</u>	<u>F</u>	<u>B</u>	-	<u>U</u>	<u>100R</u>
(1)	(2)	(3)	(4)	(5)	(6)	(7)

#### (1) SERIES

AHA Series = Lug / Threaded terminal

AHP Series = Axial lead

#### (2) POWER RATING

500= 5W	25A = 25W
10A = 10W	50A = 50W

#### (3) TOLERANCE

$F = \pm 1\%$	J= ±5%
G = +2%	$K = \pm 10\%$

#### (4) PACKAGING

B = Bulk

#### (5) TEMPERATURE COEFFICIENT OF RESISTANCE

E=±50ppm/°C,	G=±200ppm/°C
F=±100ppm/°C,	- = Based on spec.

#### (6) TYPE

Optional code, represents specific requirement,

Example:

U = Resin glue filling

W = Silicone sealant filling

Null = Quartz filling, resin glue sealing


#### (7) RESISTANCE VALUE

E24 & E96 Series


Example:

 $1R = 1\Omega$ ,  $10R = 10\Omega$ ,  $100R = 100\Omega$ 

# **DIMENSIONS**




TYPE		DIMEN	SIONS										I	Unit: mm
Normal	L1±1.5	L2±0.5	L3±0.5	A±0.5	B±0.5	C±0.5	ØE±0.3	S±1.0	H±1.0	P±1.0	H1±1.0	K±0.3	M±0.05	N±0.3
AHA500	28.6	15.2	11.5	16.4	12.5	8.5	2.4	8.1	3.8	6.7	1.7	2	1.5	1.3
AHA10A	34.9	19	14.2	20.3	15.9	10.7	2.4	9.9	4.2	7.95	1.9	2.4	2	2.2
AHA25A	49.2	27	18.2	27.4	19.8	14	3.2	13.9	5.9	11.1	1.9	4.4	2	2.2
AHA50A	70.6	50	40	29	21.4	16	3.2	15.5	6.6	10.3	2.2	5	2	2.2



TYPE		DIMEN	SIONS										Unit: mm
Normal	L1±3.0	L2±0.5	L3±0.5	A±0.5	B±0.5	C±0.5	ØE±0.3	S±1.0	H±1.0	P±3.0	H1±1.0	K±0.3	M±0.05
AHP500	71.2	15.2	11.5	16.4	12.5	8.5	2.4	8.1	3.8	28	1.7	2	0.8
AHP10A	75	19	14.2	20.3	15.9	10.7	2.4	9.9	4.2	28	1.9	2.4	0.8
AHP25A	83	27	18.2	27.4	19.8	14	3.2	13.9	5.9	28	1.9	4.4	0.8
AHP50A	106	50	40	29	21.4	16	3.2	15.5	6.6	28	2.2	5	0.8

# **DERATING CURVE**



# **ELECTRICAL CHARACTERISTICS**

CHARACTERISTICS	AHA500 AHP500	AHA10A AHP10A	AHA25A AHP25A	AHA50A AHP50A	
Power Rating on std. heatsink at at 25°C	5W	10W	25W	50W	
Power Rating without heatsink at 25°C	3W	8W	12.5W	20W	
Standard Heatsink Surface area (cm <sup>2</sup> )	415	415	535	995	
Standard Heatsink Thickness (mm)	1	1	1	1	
Voltage Proof on Insulation (Vrms)	1000	1000	1000	1000	
Voltage Proof on Insulation (Vrms) (Resin glue filling)	1000	1000	2000	2000	
Voltage Proof on Insulation (Vrms) (Silicone sealant filling)	1000	1000	1000	2000	
Resistance Range	0.1Ω~1ΚΩ	0.1Ω~1.5ΚΩ	0.1Ω~5.1ΚΩ	0.1Ω~15ΚΩ	
Maximum Working Voltage	√(P X R)				
Insulation Resistance	>100ΜΩ				
Climatic Category	55/200/56				
Operating Temp. Range	- 55°C to +275°C				
Temperature Coefficient	±50ppm/°C, ±	100ppm/°С, ±200ppı	m/°C		

Note: For resistance value out of above range is by request.

#### **TEST AND REQUIRMENTS**

TEST	TEST METHOD	PROCEDURE	APPRAISE
Short Time Overload	IEC 60115-1 4.13	5 times of rated power for 5 sec.	±1.0%+0.05Ω
Voltage Proof on Insulation	IEC 60115-1 4.7	In V-Block for 60 sec. test voltage as above table	No Breakdown
Temperature Coefficient	IEC 60115-1 4.8	Between -55°C to +275°C	Ву Туре
Insulation Resistance	IEC 60115-1 4.6	In V-Block for 60 sec.	>100ΜΩ
Solderability	IEC 60115-1 4.17	245±5°C for 3±0.5 Sec.	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5±0.5 Min. with ultrasonic	No deterioration of coatings and markings
Robustness of Terminations	IEC 60115-1 4.16	Pull test (30 Sec. Min): 5W: 1kg, 10W: 2.3kg, 25 - 50W: 4.5kg	±0.2%+0.05Ω
Damp Heat Steady State	IEC 60115-1 4.24	40±2°C,90-95% RH for 56 days, loaded with 0.1 times RCWV(or Umax., whichever less)	±5.0%+0.05Ω
Endurance at 70°C	IEC 60115-1 4.25	70±2°C at RCWV(or Umax., whichever less) for 1,000 Hr.(1.5 Hr.on,0.5 Hr. off)	±5.0%+0.05Ω
Temperature Cycling	IEC 60115-1 4.19	-55°C → Room Temp. → +155°C → Room Temp.(5 cycles)	±1.0%+0.05Ω
Resistance to Soldering Heat	IEC 60115-1 4.18	260±3°C for 10±1 Sec., immersed to a point 3±0.5mm from the body	±1.0%+0.05Ω

Note:.

#### **RCWV (Rated Continuous Working Voltage):**

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

 $V=\sqrt{(P X R)}$ 

or max. working voltage whichever is less

Where

V=Continuous rated DC or

AC (rms) working voltage (V)

P=Rated power (W)

R=Resistance value  $(\Omega)$ 




# **BULK PACKING**

Unit: Piece

Normal	PACKAGE	Quantity	
AHA500 AHP500	Bulk	540	
AHA10A AHP10A	Bulk	360	
AHA25A AHP25A	Bulk	200	
AHA50A AHP50A	Bulk	126	

#### **MARKING**



# YAGEO = Brand 1916 = Date code 10W = Power rating 10R = Resistance J = Tolerance

**Aluminum Resistors** 

AHA, AHP

# **REVISION HISTORY**

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
Version 1	Aug.31 , 2023	-	- Update legal disclaimer
Version 0	Aug.2 , 2021	-	- First issue of this specification

<sup>&</sup>quot;Yageo reserves all the rights for revising the content of this datasheet without further notification, as long as the products itself are unchanged. Any product change will be announced by PCN."

#### **LEGAL DISCLAIMER**

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non -infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.

