



SEC:A-A

SEC:B-B

SEC:C-C

SPECIFICATIONS

- 1.Voltage rating: 250V AC, DC
- 2.Current rating: 10A, AC, DC
- 3.Withstanding Voltage: 1500V AC/minute
- 4.Insulation resistance:1000M min
- 5.Temperature range: -25 ° C+85 ° C
- 6.Contact resistance: 10m max

TERMINAL

Material:Phosphor Bronze or Brass
 Finish: Plated Tin or Plated Gold
 Applicable wire: AWG#14-#20
 Used in :P5082 SERIES HOUSING
 Qty/Reel: 8000PCS
 Part No.: T5082BS-2

00=镀金 2=镀锡

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
T5082BS-2	AWG#14-#20	3.80mm(MAX.)	Brass	Tin-plated	8,000 pcs
T5082PS-2	AWG#14-#20	3.80mm(MAX.)	Phosphor Brass	Tin-plated	8,000 pcs

TOLERANCE UNLESS OTHERWISE			DRAWN	CK tan	XFCN兴飞连接器有限公司 CONNECTORS XFCN CONNECTORS CO., LTD.		SHEET	1/1
X.	±0.30	X° ±5°	CHKD				DATE	2010.4.12
.X	±0.20	.X° ±2°	APPD		PRODUCT NAME	5.08mm Crimp Style Connectors	UNITS	mm
.XX	±0.08	.XX° ±1°			PART. NO.	T5082BS-2	SCALE	1:1
AO	VER	MODIFICATION	DRAW	DATE	.XXX	±0.03 .XXX° ±0.5°	DWG NO.	009