



SPECIFICATIONS

Rated Current : 1.0AMP
 Contact Resistance : 20mΩ Max
 Withstand Voltage : 500V AC/DC
 Insulation Resistance : 1000MΩ Min
 Operation Temperature : -40°C to +105°C

Contact Material : Brass
 Contact Plating : Au or Sn Over Ni
 Insulator Material : Polyester(UL94V-0)
 Standard : PA6T
 Max Processing Temp : 230°C for 30-60 seconds
 (230°C for 5-10 seconds)

MODEL: BH-1.27S-5.6×5.7E-2XnP	DRAWN BY : <i>Leiqin</i>	DATE:
TITLE : 1.27筒牛 H5.7 SMT 大小柱	CHECKED BY : <i>Liwei</i>	DATE:
DRAWING NO:	REV. : A	APPROVED BY: <i>Wuxin</i>
SHEET: 1 OF 1	SCALE: 3:1	SIZE: A4 UNIT : mm

GENERAL TOLERANCE: (UNLESS SPECIFIED)	X: ±0.30mm	X: ±	3'
	X.X ±0.25mm	X.X' ±	2'
	X.XX ±0.20mm	X.XX' ±	1'
	X.XXX±0.10mm	X.XXX' ±	0.5'

MEASURE POINT:
 QUADRANT POINT (QP)
 TANGENCY POINT (TP)
 INTERSECTION POINT (IP)



深圳市吉威电子有限公司
深圳市元吉威电子有限公司

NO:	PARTICULAR	BY	DATE
REVISIONS			
1			
2			
3			
4			
5			
6			
7			
8			