

技术要求

使用条件:-40~55℃

Rated load: DC 30v0.5A

额定负荷:DC 30V0.5A

Contact resistance: $< 0.03 \, \Omega$

接触电阻: $<0.03\Omega$

Insulation resistance: 2100m Ω dc250v

绝缘电阻:2100MΩ DC250V

Withstand voltage: AC 500V (50Hz) / min



耐压:AC 500V(50Hz)/min

Plugging force: 3 ~ 20n

插拔力:3~20N

mechanical life: 5000 times

机械寿命:5000次



6	Cover plate	1PCS	PBT	Yellow
5	Pedestal	1PCS	PA66	
4	Pin	1PCS	Brass	Ni
3	Static contact piece	1PCS	Brass	Sn
2	Moving contact piece	1PCS	Sus	Sn
1	Pin Pin	1PCS	Brass	Sn
N0	Name	PCS	Material Science	Remarks

ΔX		日期
ΔX		
ΔX		
MARK		DESCR

ANGLAR						$\pm 5^\circ$
ΔX					$L \leq 4$	± 0.2
ΔX					$4 < L \leq 16$	± 0.3
ΔX					$16 < L \leq 63$	± 0.4
MARK		DESCRIPTION	DATE	REVISED	APPROVED	$L > 63$ ± 0.5
UNSPECIFIED TOLERANCES						

XKLE

XKB INDUSTRIAL PRECISION CO.,LIMITED

DSND		SCALE: N/A	MODEL TYPE: DC POWER JACK		
DWN		VIEW: 	PART NO.: DC-012B-2.5A-2.0		
CHKD		UNIT: mm/in	DWG NO.:		
APPD		SIZE: A4			
L. PRECISION CO., LIMITED			WEIGHT	SHEET	REVISI
				1/1	A0