



P.C.B LAYOUT

## SPECIFICATIONS

Rated Current : 3.0AMP  
 Contact Resistance : 20mΩ Max  
 Withstand Voltage : 500V AC/DC  
 Insulation Resistance : 1000MΩ Min  
 Operation Temperature : -40°C to +105°C

Contact Material : Brass  
 Contact Plating : Au or Sn Over Ni  
 Insulator Material : Polyester(UL94V-0)  
 Standard : PA6T  
 Max Processing Temp : 230°C for 5-10 seconds

MODEL: 2.00S-2XnP-H2.0E-PA4 PC6.5	DRAWN BY : <i>Leiqin</i>	DATE:	GENERAL TOLERANCE: (UNLESS SPECIFIED)
TITLE : 双排单层塑高2.0带柱贴片排针	CHECKED BY : <i>Liwei</i>	DATE:	X. ±0.30mm X: ± 3'
DRAWING NO:	REV. : A	DATE:	X.X ±0.25mm X.X' ± 2'
SHEET: 1 OF 1	SCALE: 3:1	DATE:	X.XX ±0.20mm X.XX' ± 1'
	SIZE: A4	DATE:	X.XXX±0.10mm X.XXX' ± 0.5'
	UNIT : mm	DATE:	

MEASURE POINT:

QUADRANT POINT (QP)  
 TANGENCY POINT (TP)  
 INTERSECTION POINT (IP)



深圳市吉威电子有限公司  
 深圳市元吉威电子有限公司