

Silicon NPN Power Transistors

BDV65/65A/65B/65C

DESCRIPTION

- With TO-3PN package
- Complement to type BDV64/64A/64B/64C
- DARLINGTON
- High DC current gain

APPLICATIONS

- For use in general purpose amplifier applications.

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter




Fig.1 simplified outline (TO-3PN) and symbol

Absolute maximum ratings($T_c=25^{\circ}\text{C}$)

SYMBOL	PARAMETER		CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	BDV65	Open emitter	60	V
		BDV65A		80	
		BDV65B		100	
		BDV65C		120	
V_{CEO}	Collector-emitter voltage	BDV65	Open base	60	V
		BDV65A		80	
		BDV65B		100	
		BDV65C		120	
V_{EBO}	Emitter-base voltage		Open collector	5	V
I_C	Collector current			12	A
I_{CM}	Collector current-peak			15	A
I_B	Base current			0.5	A
P_C	Collector power dissipation		$T_c=25^{\circ}\text{C}$	125	W
			$T_a=25^{\circ}\text{C}$	3.5	
T_j	Junction temperature			150	$^{\circ}\text{C}$
T_{stg}	Storage temperature			-65~150	$^{\circ}\text{C}$

Silicon NPN Power Transistors

BDV65/65A/65B/65C

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	BDV65	I _C =30mA, I _B =0	60			V
		BDV65A		80			
		BDV65B		100			
		BDV65C		120			
V _{CEsat}	Collector-emitter saturation voltage		I _C =5A, I _B =20mA			2.0	V
V _{BE}	Base-emitter on voltage		I _C =5A; V _{CE} =4V			2.5	V
I _{CBO}	Collector cut-off current	BDV65	V _{CB} =60V, I _E =0 V _{CB} =30V, I _E =0; T _C =150°C			0.4 2.0	mA
		BDV65A	V _{CB} =80V, I _E =0 V _{CB} =40V, I _E =0; T _C =150°C			0.4 2.0	
		BDV65B	V _{CB} =100V, I _E =0 V _{CB} =50V, I _E =0; T _C =150°C			0.4 2.0	
		BDV65C	V _{CB} =120V, I _E =0 V _{CB} =60V, I _E =0; T _C =150°C			0.4 2.0	
I _{CEO}	Collector cut-off current	BDV65	V _{CE} =30V, I _B =0			2	mA
		BDV65A	V _{CE} =40V, I _B =0				
		BDV65B	V _{CE} =50V, I _B =0				
		BDV65C	V _{CE} =60V, I _B =0				
I _{EBO}	Emitter cut-off current		V _{EB} =5V; I _C =0			5	mA
h _{FE}	DC current gain		I _C =5A; V _{CE} =4V	1000			
V _{EC}	Diode forward voltage		I _E =10A			3.5	V

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal resistance junction to case	1.0	°C/W

Silicon NPN Power Transistors

BDV65/65A/65B/65C

PACKAGE OUTLINE




Fig.2 Outline dimensions(unindicated tolerance: $\pm 0.1\text{mm}$)