



SPECIFICATIONS
 Rated Current:3.0AMP
 Contact Resistance:20mΩMax
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩMin
 Operation Temperature:-40°C to +105°C

Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Resistance To Soldering Heat:
 245°C±5°C, 10s(PBT insulator)
 260°C±5°C, 10s(PA6T insulator)

Ordering Information

HC-NJ 254 - * - N - * - * - * - *

| | | | | | | | |
|----------------------------|------------------------|------------------------------|----------------------------|---|------------------|----------------------------|---|
| No. of Rows 2= Dual Row | No. of Pins 6-64Pin | Type 1=ST 2=ST 3=SB | Length (Metric) (10.16) | Contact 00=Gold 01=1u" Gold 02=3u" Gold 03=5u" Gold 04=10u" Gold 05=15u" Gold 06=30u" Gold S0=Gold Flash/Tin S1=Ti | Plating Flash | Color B=Black G=Grey | Latch Type L=Long Latch S=Short Latch N= Without Latch |
|----------------------------|------------------------|------------------------------|----------------------------|---|------------------|----------------------------|---|

| | | | | | | | | | | | |
|-----------|------------------------|-------------------|------------------|-------|-------------------|--|---|--|----------------------------|--------------|-----|
| | | | GENREL TOLERANCE | | 制 图 DRAWING | | 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD | | | | |
| | | | DIM | TOL | 审 核 CHECK | | 产品名称 TITLE | | 2.54 牛角 直针 | 版本 REV. | A |
| | | | X. X | ±0.30 | 批 准 APPROVAL | | 产品料号 PART NO. | | HC-NJ254-2-N-Z-27.8-XX-X-L | 单 位 UNITS | mm |
| | | | X. XX | ±0.20 | 比 例 SCALE | | 材 料 MATERIAL | | | 页 次 SHEET | 1/1 |
| | | | X. XXX | ±0.10 | 投 影 Projection | | | | | | |
| 序号 No. | 变更内容 MODIFY CONTENT | 日期 MODIFY DATE | Angle | ±3.0° | | | | | | | |