



# SPECIFICATIONS

- Current Rating: 3Amps
- Insulation Resistance: 1000MΩ Min
- Contact Resistance: 20MΩ Max
- Withstanding Voltage: AC 1000V
- Operation Temperature: -40° to +105°
- Contact Material: Brass
- Standard: PBT
- Insulator Material: Polyester (UL 94V-0)
- Contact Plating: Gold Flash
- Max. Processing Temp: 200° C for 30-60 seconds (220° C for 5 seconds)



|  |         |  |         |          |          |       |     |            |                    |     |  |
|--|---------|--|---------|----------|----------|-------|-----|------------|--------------------|-----|--|
| UNLESS OTHERWISE SPECIFIED TOLERANCE   |         | DRAWN NAME: 2.54DC2-NP in H17 180度 PC3.8 PBT |         |          |          |       |     |            |                    |     |  |
| X  | : ±0.30 | X°   | : ±5°   | SIZE     | A4       | SCALE | N:1 | PROUCT NO. | ZX-IDC2.54-2-20PZN |     |  |
| X.X  | : ±0.25 | X.X°   | : ±1°   | REV      | A        | UNIT  | mm  | PROJECT    | PAGE 1/1           |     |  |
| X.XX   | : ±0.20 | X.XX°  | : ±0.5° | CHECKED: | CHECKED: |       |     | / /        | APPROVED:          | / / |  |
| THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHENZHEN YIXINYING TECHNOLOGY CO., LTD AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF SHENAHEN YIXINYING TECHNOLOGY CO., LTD |         |  |         |          |          |       |     |            |                    |     |  |