





FEATURES

- 360° welds (element and N-connector)
- Internal line feeding the driven element
- Analyzer-tuned best power match/lowest VSWR
- High quality mounting kit (stainless steel hardware, vertical or horizontal)

Y(B)8063

Directional Yagi Antenna 806-896 MHz

Our premium series directional Yagi antennas are fully gold anodized for corrosion resistance. All UHF and above frequency antennas feature internal matching to assure broad bandwidth and resistance to severe weather. There is no gamma match to ice up, corrode or detune. Our engineering staff has optimized the product family for forward gain by computer analysis and then field-tested each for conformance.

MARKETS

- Point-to-point and multi-point/omni outdoor antennas
 applications
- Transportation (i.e. railroad switching), remote location monitoring (i.e. oil fields, weather, and utility meters)


ELECTRICAL SPECIFICATION		
Operating Frequency (MHz)	806-896	
Number of Ports	1	
Gain (dBi)	8.15	
Nominal Impedance (Ohms)	50	
Max Power - Ambient 25°C (W)	500	
Front-to-Back Ratio (dB)	17.15	

MECHANICAL SPECIFICATION		
Dimensions - diameter - mm (inches)	9.525 x 425.45 (3/8" x 16.75")	
Element Material	6061-T6 aluminum rod	
Boom Material	Heat-treated 6061-T6 aluminum tube	
Mounting Hardware Material	Stainless Steel	
Radiating Elements	3	
Lightning Protection	DC Grounded	

ENVIRONMENTAL SPECIFICATION		
Wind Survival - km/hr (mph)	160.93 (100)	

PART NUMBER	COLOR	CABLE LENGTH	CONNECTOR
Y8063	Aluminum	N/A	N-Female
YB8063	Black	N/A	N-Female

RADIATION PATTERNS



Normalized to 7.1dBd

Vertical-to-vertical polarization

Vertical-to-Horizontal polarization

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31(0)73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use.

TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

11/21 Original



