



SPECIFICATIONS:

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Tin over Nickel
 SMT Material: Brass/Tin over Nickel
 Material: LCP, UL94V-0(Ivory)

Ordering Information & Dimensions

Part NO.	Dimensions(mm)		
	A	B	C
A2501WV-S-2P	2.50	6.00	10.00
A2501WV-S-3P	5.00	8.50	12.50
A2501WV-S-4P	7.50	11.00	15.00
A2501WV-S-5P	10.00	13.50	17.50
A2501WV-S-6P	12.50	16.00	20.00
A2501WV-S-7P	15.00	18.50	22.50
A2501WV-S-8P	17.50	21.00	25.00
A2501WV-S-9P	20.00	23.50	27.50
A2501WV-S-10P	22.50	26.00	30.00
A2501WV-S-11P	25.00	28.50	32.50
A2501WV-S-12P	27.50	31.00	35.00
A2501WV-S-13P	30.00	33.50	37.50
A2501WV-S-14P	32.50	36.00	40.00
A2501WV-S-15P	35.00	38.50	42.50
A2501WV-S-16P	37.50	41.00	45.00

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	4:1	1 of 1
DRWN	CHK'D	APPR
Dengchun Yi	Diankui Wan	Jack Yin

TITLE
**2.50mm PITCH
 VERTICAL HEADER
 -SMD TYPE**

A2	MODIFY DRAWING	2021.10.25
A1	CHANGE THE DRAWING	2020.05.13
A0	NEW RELEASE	2011.05.13
REV	DESCRIPTION	DATE

General Tolerances
 x.x±0.25
 x.xx±0.20
 x.xxx±0.15
 ANGLES ±1°



DRAWING NO.	REV
A2501WV-S-XP	A2