






Nov.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



A-A (50:1)



ENGAGEMENT FIGURE (50:1)




- NOTE
1. ALL LEAD CO-PLANARITY SHALL BE 0.08mm MAX.
 2. CONTACT PLATING SPECIFICATIONS.
CONTACT AREA : GOLD 0.05 μ m MIN.
SMT LEAD : GOLD 0.05 μ m MIN.
UNDER PLATING : NICKEL 1 μ m MIN.
(SURFACE : SEALING)
 3. METAL FITTING PLATING SPECIFICATIONS.
SMT LEAD : GOLD 0.05 μ m MIN.
UNDERPLATING : NICKEL 1 μ m MIN.
(SURFACE : SEALING)
 4. HRS MARK AND CAV No. ARE INDICATED IN APPROX POSITION SHOWN.
 5. A PART OF THE WALL COULD BE NOTCHED.

	COUNT	DESCRIPTION OF REVISIONS	B	Y	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	B	Y	CHKD	DATE
△								△					
△								△					
△								△					


4	PS	CLEAR (EMBOSSED CARRIER TAPE)						7	PS	CLEAR (REINFORCEMENT COLLAR)				
3	COPPER ALLOY	3						6	PS	BLACK (PLASTIC REEL)				
2	COPPER ALLOY	2						5	POLYESTER	CLEAR (COVER TAPE)				
1	LCP	UL94 V-0, BLACK												
NO.	MATERIAL	FINISH , REMARKS						NO.	MATERIAL	FINISH , REMARKS				
REMARKS								DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
								J. S. PARK	J. S. PARK	H. W. JO	T. S. KANG	17. 08. 09		
								17. 08. 09	17. 08. 09	17. 08. 09	17. 08. 09			
CODE NO. (OLD)	SCALE	DRAWING NO.						PART NO.	BM23FR0.6-8DP-0.35V(895)					
	10:1	EDC3-632160						CODE NO	CL 6644-0074-0-895					
	UNITS	HRS HIROSE KOREA CO., LTD.												
	mm													

7 RECOMMENDED PCB LAYOUT




RECOMMENDED METAL MASK DIMENSIONS

METAL MASK THICKNESS : $100 \mu\text{m}$



6 RECOMMENDED REFLOW TEMPERATURE PROFILE USING LEAD-FREE SOLDER PASTE.



REFLOW METHOD: N_2 REFLOW
NUMBER OF REFLOW CYCLES: 2 CYCLES MAX.


- 1) REFLOW TIME
DURATION ABOVE 220°C , 60 SEC MAX.
(PEAK TEMPERATURE: 250°C MAX)
- 2) PRE-HEAT TIME
PRE-HEAT TEMPERATURE (MIN): 150°C
PRE-HEAT TEMPERATURE (MAX): 180°C
PRE-HEAT TIME: 90-120 SEC.

- 6 THIS TEMPERATURE PROFILE IS PER THE CONDITIONS SHOWN ABOVE. ADDITIONAL FACTORS, SUCH AS SOLDER PASTE TYPE, PCB SIZE AND OTHER MOUNTED COMPONENTS COULD AFFECT THE PROFILE. THEREFORE, A THOROUGH EVALUATION OF MOUNTING CONDITION IS REQUIRED PRIOR TO PRODUCTION. TEMPERATURE IS MEASURED AT CONTACT LEAD.
- 7 PLEASE CONTACT US IN CASE YOU WILL MAKE DIFFERENT SETTINGS FROM OUR RECOMMENDATION.


	DRAWING NO.	EDC3-632160	PART NO.	BM23FR0.6-8DP-0.35V(895)
	SCALE	10:1	CODE NO	CL 6644-0074-0-895
	UNITS	mm		2/3

Nov.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

EMBOSSED CARRIER TAPE PACKAGING (5:1)




C-C (5:1)




DIRECTION OF UNREELING


B-B (5:1)




10 TAPING(FREE)



STYLE AND DIMENTION OF REEL (FREE)



E-E (FREE)



DETAIL OF PART No. LABEL

SUPPLIER	HIROSE ELECTRIC CO., LTD.
QUANTITY	1,000
PART NO.	BM23FR0. 6-8DP-0. 35V(895)
CODE NO.	CL 6644-0074-0-895
DATE OF MANUFACTURED	2023. 10. 1
生産月日	年 月 日
図番	** ** *
品名	BM23FR0. 6-8DP-0. 35V(895)
納入数量	1,000個
納入者	HIROSE KOREA

8 . PER REEL 1,000 CONNECTORS.

9 . THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

10 REFER TO JIS C 0806, IEC-60286-3 (PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING)

11 AFTER PACKAGING, ROLL 2 METERS OF THE REINFORCEMENT COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL POCKET. AND TAPE DOWN AT THE END THE COLLAR.

DRAWING NO.	EDC3-632160	PART NO.	BM23FR0. 6-8DP-0. 35V(895)
SCALE	10:1	CODE NO	CL 6644-0074-0-895
UNITS	mm		
HRS	HIROSE KOREA CO., LTD.		