



Fused Terminal Blocks

1003 SI/ 1 DS GW

screw terminal block with fuse holder 6,3x25/6,3x32, 1 pole, cross-section rating: 4.0 mm², voltage rating: 500 V, current rating: 16 A



Order Info

reference number (ref.no.)	11618
PU	100
EAN	4028012143993

Type

type	screw terminal block with fuse holder 6,3x25/6,3x32
number of poles	1 pole
clamping units per pole	1
cross-section rating	4.0 mm ²
connection type	screw

Technical Data

voltage rating	500 V
current rating	16 A
insulating material	PA GW
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	4.0 mm ²
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
assembly contact screw	0.8x4.0 / ⚙ 0.8 Nm
type of conductor solid external	yes
type of conductor flexible external	yes
type of conductor stranded external	yes
type of conductor solid internal	yes
type of conductor stranded internal	yes
type of conductor flexible internal	yes

Approvals

acc. to EN 60127	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF