


DIN41612 B Type Female

深圳市威尔杰电子有限公司



Material:



Housing: Thermoplastic Polyester Glass Filled UL94V-0.
Contacts: Copper Alloy.

Electrical Characteristics:


Current Rating: 2 A.
Dielectric Withstanding Voltage: AC 1000V .
Insulator Resistance: 1000MΩ min.
Contact Resistance: 20mΩ max.
Operating Temperature: -55°C ~+125°C.

Features:




* Mates with Male 2Row
9001-3164,3132 B Type.
9001-3364,3332 Q Type.



Dip Type



Press Fit Type



P.C. Board Layout

Length	1	2	W1	W2
X	4.0	2.5	13	17
Y	4.6	6.3	13	17
Pitch	Position	Rows with Contacts	Contact Arrange	
2.54mm	64	a b		
	32	a -		
5.08mm	32	a b		
	16	a -		


9001- 3 2 64 1 C 00 P L1 A

Series 3: 2.54mm 2: Female Position 1: Dip Length 2: Dip Length C: Selective 00: G/F Blank: Dip L1: With Lock A: Tray


4: 5.08mm W1: Dip Length Gold Plated P: Press Fit Lock Package

W2: Dip Length See Page CA03


2 Row insulator
B (Standard mounting)
Mounting axis
of the connector




3 Row insulator
C (Standard mounting)
Mounting axis
of the connector




Board lock available
L1=P.C.B. Thickness 1.6 ~2.0 mm
L2=P.C.B. Thickness 2.8 ~3.2 mm




Q (Reverse mounting)
Mounting axis
of the connector



R (Reverse mounting)
Mounting axis
of the connector




Board lock available
L1=P.C.B. Thickness 1.6 ~2.0 mm
L2=P.C.B. Thickness 2.8 ~3.2 mm




I.D.C. Type Ribbon Cable



2 Row insulator



3 Row insulator



Press Fit Type
2 Row insulator



3 Row insulator

