



Screw-Screwless Connectors

900-07 RZ/ 3

Terminal Block, 3 pole, fixing: catch pin, clamping units per pole: 2, voltage rating: 450 V, current rating: 17.5 A, cross-section external: 2.5 mm², cross-section internal: 1.5 mm²



Order Info

reference number (ref.no.)	114803
PU	800
EAN	4028012104888

Type

type	Terminal Block
number of poles	3 pole
clamping units per pole	2
cross-section rating	1.5 / 2.5 mm ²
connection type	screw plug-in

Technical Data

voltage rating	450 V
current rating	17.5 A
insulating material	PA
contact material	spring steel, steel
flammability rating	V-2
max. ambient temperature operation	85 °C
assembly contact screw	0.8x4.0 / ⌀ 0.5 Nm
wall thickness min.	0.5 mm
wall thickness max.	1.4 mm
internal core cross-section min.	0.5 mm ²
internal core cross-section max.	2.5 mm ²
internal stripping length	7.0-7.5 mm
external stripping length	8.0-8.5 mm
fixing	catch pin
type of conductor solid external	yes
type of conductor flexibel external	yes
type of conductor solid internal	yes
type of conductor stranded internal	yes
cross-section external	2.5 mm ²
cross-section internal	1.5 mm ²

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

ZEL 110	196420
---------	--------