

Data sheet

16099.2 GSM-PRO



Compact reporting system for mobile networks, for monitoring analogue and digital values and remotely switching relay outputs. Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Business data

Article number	<u>16099.2</u>
Article name	GSM-PRO
GTIN (EAN)	4044211151560
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	221 g
Weight per piece (including packaging)	263 g
Unit of weight	G
Customs number	85176990
Country of origin	NL
Product description	Controller module

Data sheet

16099.2 GSM-PRO

Technical data

Dimensions

Length	88 mm
--------	-------

Width	95 mm
-------	-------

Connection data

Connection principle	Screw connection
----------------------	------------------

Wire cross-section single core (rigid), min.	0.2 mm ²
--	---------------------

Wire cross-section single-core (rigid), max.	2.5 mm ²
--	---------------------

Wire cross-section stranded, min.	0.2 mm ²
-----------------------------------	---------------------

Wire cross-section stranded, max.	2.5 mm ²
-----------------------------------	---------------------

Stripping length	6 mm
------------------	------

Torque	0.4 Nm
--------	--------

Output data

Number of outputs	4
-------------------	---

Switching voltage / switching voltage max.	250 / 250 VAC
--	---------------

Continuous current max. / Inrush current max.	5 / 5 A
---	---------

Switching capacity, max.	1200 VA
--------------------------	---------

Switching frequency, max.	6/min kHz
---------------------------	-----------

Electrical lifespan (AC1)	1,5x10 ⁵
---------------------------	---------------------

Mechanical lifespan	15x10 ⁶
---------------------	--------------------

Relay contact	1CO
---------------	-----

GSM data

2G	Quad-band GSM bands: 850, 900, 1800 and 1900 MHz
----	--

Antenna GSM	50 ohm, SMA plug
-------------	------------------

Further technical data

Power supply	10-30 VDC -
--------------	-------------

Current consumption	275 @ 24 VDC mA
---------------------	-----------------

Protection class	IP20
------------------	------

Storage temperature, min.	-20 °C
---------------------------	--------

Storage temperature, max.	70 °C
---------------------------	-------

Mounting	Mounting rail TS35 / direct mount
----------	-----------------------------------

Backup power	Internal maintenance-free supercap capacitor
--------------	--

Electromagnetic properties	Directive 2014/30/EC in compliance with EN 55011 and EN 61326-1
----------------------------	---

Data sheet

16099.2 GSM-PRO



Technical data

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Approvals

Standards and regulations

Standards / specifications

Low-Voltage Directive (LVD) 2014/35/EC, in compliance with EN 50178. EMC Directive 2014/30/EC, in compliance with EN 61326-1

Media

Accessories

Antennas

Connection cables



USB 2.0 connection cable [1 USB 2.0 plug A - 1 USB 2.0 plug Mini-B angled 90°] Cable length: 1.8 m, gold-plated plug contacts, colour: black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16103.2</u>	GSM-USB-Cable	4044211151584	1 ST