

**Driver LCO 25W 350/500/700/1050/1400mA 0-10V C ADV UNV**  
OUTDOOR advanced series

**Product description**

- \_ Constant current LED driver
- \_ Only for US applications
- \_ Dimmable via 0 ... 10 V interface
- \_ Dimming range 10 to 100 %
- \_ Class 2 power supply (not the 350 mA version)
- \_ FCC Part 15
- \_ Type HL rated for hazardous location
- \_ Dry and damp location
- \_ Max. output power 25 W
- \_ Up to 87 % efficiency
- \_ Nominal lifetime up to 100,000 h
- \_ 5 years guarantee (conditions at [www.tridonic.com](http://www.tridonic.com))

**Housing properties**

- \_ Casing: polycarbonate, black
- \_ Potted style
- \_ Type of protection IP66

**Functions**

- \_ Over voltage protection
- \_ Short-circuit protection
- \_ No-load protection

**Typical applications**

- \_ For bollard, landscape and commercial fixtures

**Website**

<http://www.tridonic.us/28002143>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street




Decorative

**Driver LCO 25W 350/500/700/1050/1400mA 0-10V C ADV UNV**

OUTDOOR advanced series

The complete data sheet for this product is available in the Downloads section.



Dimensions in mm / inch

**Ordering data**

| Type                           | Article number | Packaging, carton | Packaging, pallet | Weight per pc. |
|--------------------------------|----------------|-------------------|-------------------|----------------|
| LCO 25/1400/18 0-10V C ADV UNV | 28002143       | 50 pc(s).         | 1,300 pc(s).      | 0.42 lbs       |

**Technical data**

|                                                           |                         |
|-----------------------------------------------------------|-------------------------|
| Rated supply voltage                                      | 100 – 277 V             |
| AC voltage range                                          | 90 – 305 V              |
| Mains frequency                                           | 50 / 60 Hz              |
| Leakage current (at 120 V, 60 Hz, full load)              | < 300 µA                |
| Leakage current (at 277 V, 60 Hz, full load)              | < 700 µA                |
| Max. input power (at 120 V, 60 Hz, full load)             | 30.5 W                  |
| Max. input power (at 277 V, 60 Hz, full load)             | 30.5 W                  |
| λ (at 120 V, 60 Hz, full load)                            | 0.95                    |
| λ (at 277 V, 60 Hz, full load)                            | 0.92C                   |
| Typ. input current in no-load operation (at 120 V, 60 Hz) | 20 mA                   |
| Typ. input current in no-load operation (at 277 V, 60 Hz) | 20 mA                   |
| Typ. input power in no-load operation (at 120 V, 60 Hz)   | 0.9 W                   |
| Typ. input power in no-load operation (at 277 V, 60 Hz)   | 1.9 W                   |
| In-rush current (peak / duration at 120 V)                | 30 A / 3 µs             |
| In-rush current (peak / duration at 277 V)                | 50 A / 3 µs             |
| THD (at 120 V, 60 Hz, full load)                          | < 6 %                   |
| THD (at 277 V, 60 Hz, full load)                          | < 12 %                  |
| Starting time (full load)                                 | ≤ 500 ms                |
| Turn off time at full load                                | < 200 ms                |
| Output current tolerance                                  | ± 5 %                   |
| Max. output current peak (non-repetitive)                 | ≤ output current + 30 % |
| Output LF current ripple (< 120 Hz)                       | < 18 %                  |
| Dimming range                                             | 10 – 100 %              |
| Mains surge capability (between L - N)                    | 2 kV                    |
| Type of protection                                        | IP66                    |
| Lifetime                                                  | up to 100,000 h         |
| Guarantee (conditions at www.tridonic.com)                | 5 Year(s)               |
| Dimensions L x W x H                                      | 3.78 x 2.8 x 0.99 inch  |

**Approval marks**

## Standards

UL 8750, UL 1310, FCC PART 15, ANSI C62.41, ANSI C63.4, UL 1012, NEMA 4, CSA C22.2

## Specific technical data

| Type                           | Output current | Min. forward voltage | Max. forward voltage | Max. output voltage (U-OUT) | Max. output power (at 120 V, 60 Hz, full load) | Typ. power consumption (at 120 V, 60 Hz, full load) | Typ. current consumption (at 120 V, 60 Hz, full load) | Typ. efficiency (at 120 V, 60 Hz, full load) | Max. output power (at 277 V, 60 Hz, full load) | Typ. power consumption (at 277 V, 60 Hz, full load) | Typ. current consumption (at 277 V, 60 Hz, full load) | Typ. efficiency (at 277 V, 60 Hz, full load) | t <sub>c</sub> | Ambient temperature t <sub>a</sub> |
|--------------------------------|----------------|----------------------|----------------------|-----------------------------|------------------------------------------------|-----------------------------------------------------|-------------------------------------------------------|----------------------------------------------|------------------------------------------------|-----------------------------------------------------|-------------------------------------------------------|----------------------------------------------|----------------|------------------------------------|
| LCO 25/1400/18 0-10V C ADV UNV | 1,400 mA       | 9 V                  | 18 V                 | 20 V                        | 25.2 W                                         | 30.0 W                                              | 250 mA                                                | 84 %                                         | 25.4 W                                         | 30.0 W                                              | 120 mA                                                | 83.5 %                                       | 185 °F         | -22 ... +140 °F                    |