



SENTRON, Switch disconnector 3LD, main switch, 6-pole, Iu: 63 A, Operating power / at AC-23 A at 400 V: 22 kW, molded-plastic encapsulation for metric screw connection, 1 NC, 1 NO, rotary operating mechanism, black

Model	
product brand name	SENTRON
product designation	3LD Switch disconnector
design of the product	Main switch
display version / for switch position indicator manual operation	1 ON - 0 OFF
design of the actuating element	Short rotary knob
design of handle	rotary operating mechanism, black
type of the driving mechanism / motor drive	No
General technical data	
number of poles	6
number of poles / note	PE + N
type of device	fixed mounting
type of switch	Molded-plastic enclosure for metric threaded joint
size of switch disconnector	3
mechanical service life (switching cycles) / typical	100 000
electrical endurance (switching cycles)	
• at AC-23 A / at 690 V	6 000
I <sub>2t</sub> value / with closed switch / at 690 V / for combination switch + gG fuse / maximum	21 kA2.s
let-through I <sub>2t</sub> value / with closed switch / at 440 V / for combination switch + gG fuse / maximum	21 kA2.s
operating frequency / maximum	50 1/h
Voltage	
insulation voltage / rated value	690 V
surge voltage resistance / rated value	6 kV
operational current / at AC / rated value	63 A
operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
Protection class	
protection class IP	IP65
degree of protection NEMA rating	1, 4X, 12
protection class IP / on the front	IP65
Dissipation	
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	4.5 W
• per conductor / typical	4.5 W

Current	
operational current	
• at AC-23 A / at 690 V / rated value	22 A
• at AC-23 A / at 400 V / rated value	43 A
• at AC-22 A / at 690 V / rated value	63 A
• at AC-21 / at 690 V / rated value	63 A
• at AC-21 A / at 240 V / rated value	63 A
• at AC-21 A / at 440 V / rated value	63 A
• at AC-22 A / at 240 V / rated value	63 A
• at AC-22 A / at 440 V / rated value	63 A
• at AC-23 A / at 240 V / rated value	43 A
• at AC-23 A / at 440 V / rated value	43 A
operational current / of upstream fuse / rated value	63 A
let-through current / with closed switch	
• at 440 V / for combination switch + gG fuse / maximum	6 kA
• at 690 V / for combination switch + gG fuse / maximum permissible	6 kA
short-time withstand current (Icw)	
• limited to 1 s / rated value	1 260 A
• at 690 V / limited to 1 s / rated value	1 260 A
Main circuit	
operating frequency	
• initial value	50 Hz
• full-scale value	60 Hz
operating power	
• at AC-23 A / at 240 V / rated value	11 kW
• at AC-23 A / at 400 V / at 50/60 Hz / rated value	22 kW
• at AC-23 A / at 400 V / rated value	22 kW
• at AC-23 A / at 440 V / rated value	22 kW
• at AC-23 A / at 690 V / rated value	18.5 kW
• at AC-3 / at 240 V / rated value	11 kW
• at AC-3 / at 400 V / rated value	18.5 kW
• at AC-3 / at 690 V / rated value	15 kW
operational current / rated value	63 A
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	1
number of NO contacts / for auxiliary contacts	1
operating voltage / of auxiliary contacts / at AC / maximum	500 V
continuous current / of the auxiliary contact / rated value	10 A
insulation voltage / of the auxiliary switch / rated value	500 V
Suitability	
suitability for use	
• main switch	Yes
• switch disconnector	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes
• maintenance/repair switch	Yes
Appearance	
color / of the actuating element	black
Product details	
• product function / can be locked into OFF position	Yes
number of bracket locks / maximum	3
hasp thickness / of the bracket locks / minimum	4 mm
hasp thickness / of the bracket locks / maximum	8 mm
product extension / optional	
• motor drive	No

• voltage trigger	No
<b>Short circuit</b>	
conditional short-circuit current / with line-side fuse protection • at 690 V / by gG fuse / rated value	50 kA
<b>according UL</b>	
operational current / at AC / according to UL 508/UL 60947-4-1 / rated value	63 A
operating voltage / at AC / at 50/60 Hz / according to UL 508/UL 60947-4-1 / rated value	600 V
active power [hp] / at AC / at 480 V / according to UL 508/UL 60947-4-1 / rated value	40
active power [hp] / at AC / at 600 V / according to UL 508/UL 60947-4-1 / rated value	50
short-time withstand current (SCCR) / at 600 V / according to UL 508/UL 60947-4-1	5 kA
continuous current / of upstream fuse / according to UL / rated value	175 A
type of fuse / according to UL	RK5
<b>Number</b>	
number of connectable NC contacts / for auxiliary contacts / attachable / maximum	2
number of connectable NO contacts / for auxiliary contacts / attachable / maximum	3
number of connectable CO contacts / for auxiliary contacts / attachable / maximum	0
<b>Connections</b>	
AWG number / as coded connectable conductor cross section / solid • maximum • minimum	6 14
type of connectable conductor cross-sections / for copper conductor • solid • finely stranded / with core end processing • stranded	1x (2,5...35mm <sup>2</sup> ) 1x (2,5...16 mm <sup>2</sup> ) 1x (2,5..35mm <sup>2</sup> )
type of connectable conductor cross-sections / for auxiliary contacts • solid • finely stranded / with core end processing • stranded	lateral auxiliary switch 2x (0,75 ... 2,5mm <sup>2</sup> ), 1x 4mm <sup>2</sup> ; front auxiliary switch 1x (0,75 ... 2,5mm <sup>2</sup> ) lateral auxiliary switch 2x (0,75 ... 1,5mm <sup>2</sup> ), 1x 2,5mm <sup>2</sup> ; front auxiliary switch 1x 2,5mm <sup>2</sup> lateral auxiliary switch 2x (0,75 ... 2,5mm <sup>2</sup> ), 1x 4mm <sup>2</sup> ; front auxiliary switch 1x (0,75 ... 2,5mm <sup>2</sup> )
type of electrical connection • for main current circuit • for auxiliary contacts	box terminal connection terminals
<b>Requirements</b>	
design of the fuse link • for short-circuit protection of the main circuit / required • for short-circuit protection of the auxiliary switch / required	fuse gL/gG: 63 A fuse gL/gG: 10 A
<b>Mechanical Design</b>	
height	302 mm
width	212 mm
depth	181 mm
fastening method	Complete unit in enclosure
fastening method • 4-hole front mounting • front mounting with central attachment • rail mounting	No Yes No

net weight	2 164 g
<b>Environmental conditions</b>	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature / during storage / minimum	-25 °C
<b>Certificates</b>	
reference code	
• acc. to DIN EN 61346-2	S
• acc. to IEC 81346-2	SF
<b>General Product Approval</b>	



[Miscellaneous](#)



<a href="#">Declaration of Conformity</a>	<a href="#">Test Certificates</a>	<a href="#">Marine / Shipping</a>	<a href="#">other</a>
---	-----------------------------------	-----------------------------------	-----------------------



[Special Test Certificate](#)

[Miscellaneous](#)



[Environmental Confirmations](#)

LR

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD2566-4VD51>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)






<https://support.industry.siemens.com/cs/ww/en/ps/3LD2566-4VD51>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3LD2566-4VD51](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2566-4VD51)

Tender specifications

<http://www.siemens.com/specifications>



-Cl

