

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-40°C to 105°C (Note1)	STORAGE TEMPERATURE RANGE	-40°C to 105°C	
	VOLTAGE	50 V DC	CURRENT	1 A	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS		QT AT
CONSTRUCTION					
General Examination	Visually and by measuring instrument.		According to drawing.		x x
Marking	Confirmed visually.				x x
ELECTRIC CHARACTERISTICS					
Contact Resistance	1A DC.		50mΩ max.		— —
Contact Resistance Millivolt Level Method	20 mV AC max, 0.1 mA (DC or 1000Hz).		50mΩ max.		— —
Insulation Resistance	500 V DC.		100MΩ min.		— —
Voltage Proof	500 V AC for 1 min.		No flashover or breakdown.		x x
Continuity	100 mA DC		Continuity		— x
MECHANICAL CHARACTERISTICS					
Mechanical Operation	30 times insertions and extractions.		① Contact resistance 100mΩ max ② No damage, crack and looseness of parts.		— x —
Vibration	Frequency 20 to 200 Hz, 43.1 m/s ² at 3 h for 3 directions.		① No electrical discontinuity of 10μs. ② Contact resistance: 100mΩ max. ③ No damage, crack and looseness of parts.		— — —
Shock	Frequency 20 to 50 Hz, 66.6 m/s ² at 1 h.		① No electrical discontinuity of 10μs. ② Contact resistance: 100mΩ max. ③ No damage, crack and looseness of parts.		— — —
Lock Strength	Applying a pull force the mating axially at 100N max.		① During applying, mating completely. ② After applying, no defect of mating parts.		— — —
ENVIRONMENTAL CHARACTERISTICS					
Damp Heat (Steady State)	Exposed at 60°C, 90 ~ 95 %, 500h.		① Contact resistance: 100mΩ max. ② Insulation resistance: 100MΩ min. ③ No damage, crack and looseness of parts.		— — —
Rapid Change Of Temperature	Temperature -40 → 5 to 35 → 105 → 5 to 35°C Time 30 → 5 → 30 → 5 min under 1000 cycles.		① Contact resistance: 100mΩ max. ② Insulation resistance: 100MΩ min. ③ No damage, crack and looseness of parts.		— — —
Dry Heat	Exposed at 105°C, 300h.		① Contact resistance: 100mΩ max. ② No damage, crack and looseness of parts.		— — —
Cold	Exposed at -40°C, 120h.		① Contact resistance: 100mΩ max. ② No damage, crack and looseness of parts.		— — —
Resistance To SO ₂ Gas	Exposed in 25 ppm for 96h.		① Contact resistance: 100mΩ max. ② No damage, crack and looseness of parts.		— — —
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0					
REMARK			APPROVED	KI. HIROKAWA	20211223
Note1) Include the temperature rising by current.			CHECKED	MH. YAMAGUCHI	20211223
			DESIGNED	HR. IWAI	20211223
			DRAWN	HR. IWAI	20211223
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-395704-00-00
HS	SPECIFICATION SHEET		PART NO.	WGT43GT43-1191	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0781-1191-0-00	0