HD34-24-31PT-059 ACTIVE

DEUTSCH | DEUTSCH HD, DEUTSCH HD30

TE Internal #: HD34-24-31PT-059

Housing for Male Terminals, Wire-to-Wire, 31 Position, Sealable,

Wire & Cable, Power & Signal, Panel Mount / Cable Mount (Free-

Hanging), Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HD30 Housings



Connector System: Wire-to-Wire

Number of Positions: 31

Connector & Housing Type: Housing for Male Terminals

Sealable: Yes

Mating Pin Diameter: 1.59 mm [.063 in]

All DEUTSCH HD30 Housings (358)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Circular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Contact Retainer

Configuration Features

Blank Cavity Position	0
Connector Modification	Cable Clamp
Connector Seal Code	T Seal
Number of Positions	31

Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V

Body Features



Cable Exit Angle	180°
Contact Features	
Contact Size	Size 16
Contact Type	Pin
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Not Keyed
Mating Alignment	Without
Connector Mounting Type	Cable Mount (Free-Hanging), Panel Mount
Housing Features	
Housing Material	Aluminum
Dimensions	
Connector Height	47.53 mm[1.875 in]
Product Width	50.8 mm[2 in]
Product Length	84.28 mm[3.318 in]
Compatible Insulation Diameter Range	2.23 – 2.69 mm[.088 – .106 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Degree of Protection	IP67
Packaging Features	
Packaging Quantity	80
Packaging Method	Box
Other	
Serviceable	Yes



Connector Position Assurance Capable

No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-H3930-CH8172 DEUTSCH HD30 Housings




TE Part # CAT-H3930-RC8382 Receptacle Protective Caps -DEUTSCH HD30



TE Part # CAT-D48-ST273 **DEUTSCH Solid Contacts**



TE Part # CAT-J67-DSCC16 **DEUTSCH Size 16 Crimp Contacts**



TE Part # 16-04477 GASKET, 24SZ, BLK, HD30



TE Part # CAT-H3930-M8649 Mounting Hardware for DEUTSCH HD30 Connectors



TE Part # 114017-ZZ SEALING PLUG, SIZE 12/16, WHT



TE Part # 2300908-1 0460-003-16329, PIN, SOLID, 20-24AWG, AU

TE Part # CAT-D48-SFT273 **DEUTSCH Stamped and Formed** Contacts

TE Part # 62036-40 62036 HDP24 FLANGE-SEAL silicone 60shore

Also in the Series | DEUTSCH HD



Automotive Connector Caps & Covers



Automotive Housings(742)



Connector Backshells(29)



Connector Seals & Cavity Plugs(10)



Connector Strain Relief(5)



Insertion & Extraction Tools(11)



Other Automotive Connector Accessories(11)



PCB Headers & Receptacles(1)

Also in the Series | DEUTSCH HD30





Automotive Connector Caps & Covers (14)



Automotive Housings(359)



Connector Backshells(2)



Connector Seals & Cavity Plugs(11)



Connector Strain Relief(5)



Insertion & Extraction Tools(10)



Other Automotive Connector Accessories(6)

Customers Also Bought




TE Part #HD34-24-29PE-059
DEUTSCH HD30 Housings



TE Part #DT06-12SD-EP06
PLG, 12P, BRN, N, SEAL RET,ENH KEY,
CAP,D



TE Part #5-1393127-5 PRD-11DJ0-24=PRD



24P MR II PLUG HSG V0

Documents

Product Drawings

REC,31P,AL,T, CBL CLMP BT, DRAIN,16,P,MC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HD34-24-31PT-059_99_c-hd34-24-31pt-059-99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HD34-24-31PT-059_99_c-hd34-24-31pt-059-99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HD34-24-31PT-059_99_c-hd34-24-31pt-059-99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the $\ensuremath{\mathsf{Terms}}$ and $\ensuremath{\mathsf{Conditions}}$ of us

Housing for Male Terminals, Wire-to-Wire, 31 Position, Sealable, Wire & Cable, Power & Signal, Panel Mount / Cable Mount (Free-Hanging), Hybrid



Product Specifications

Application Specification

English