



## Parallel Jaw Grip with Hot Latch



This lightweight, compact grip pulls ACSR cable from 0.16 to 0.90-Inch (2.3 to 0.4 CM) in diameter. The round jaw provides maximum contact with the cable while minimizing deformation. The hot latch closes automatically to guard against the grip accidentally disengaging from wire.

### Specifications

|                   |                                   |                    |                   |
|-------------------|-----------------------------------|--------------------|-------------------|
| Type:             | Chicago Grip                      | Application:       | Wire Pulling      |
| Special Features: | Hot Latch, Spring                 | Overall Length:    | 9.78" (24.8 cm)   |
| Overall Height:   | 2.31" (5.9 cm)                    | Overall Width:     | 7.53" (19.1 cm)   |
| Material:         | Steel                             | Cable Type:        | ACSR, AAC, Copper |
| Cable Diameter:   | 0.16" to 0.90" (4.06 to 22.86 mm) | Hot Latch:         | Y                 |
| Swing Latch:      | N                                 | Spring:            | Y                 |
| Locking Handle:   | N                                 | Jaw Type:          | Round - Serrated  |
| Jaw Length:       | 5" (12.7 cm)                      | Maximum Safe Load: | 5000 lb (2268 kg) |
| Weight:           | 7.8 lb (3.5 kg)                   |                    |                   |