3503G2B178RFTD V ACTIVE

CGS | CGS 3503 TE Internal #: 5-2176526-3 178 Ω , Thin Film, Power Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, 2 W, ±50 ppm/°C, Solder, 3.05 x 1.55 x .43 mm, CGS 3503 View on TE.com >

Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Power Resistor

Number of Terminations: 2

Package Size Code: 1206

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

Features

Product Type Features



Resistor Type	Power Resistor
Package Size Code	1206
Element Type	Thin Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Operating Voltage	100 V
Passive Component Tolerance	1 %
Resistance Class	Up to 1kΩ
Resistance Value	178 Ω
Power Rating	2 W
Termination Features	
Number of Terminations	2
Surface Mount Resistor Termination Type	Solder

3503G2B178RFTD

178 Ω, Thin Film, Power Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, 2 W, ±50 ppm/°C, Solder, 3.05 x 1.55 x .43 mm, CGS 3503



Dimensions

Passive Component Dimensions	3.05 x 1.55 x .43 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C

Temperature Coefficient

Packaging Features

Packaging Method

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in

-55 – 155 °C

±50 ppm/°C

Taped & Reeled

other sources.

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts


3503G2B178RFTD

178 Ω , Thin Film, Power Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, 2 W, ±50 ppm/°C, Solder, 3.05 x 1.55 x .43 mm, CGS 3503





Also in the Series | CGS 3503



Customers Also Bought



Documents

Product Drawings 3503G 2B 178R 1% 5K RL

English

CAD Files

Customer View Model ENG_CVM_CVM_5-2176526-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-2176526-3_A.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_5-2176526-3_A.2d_dxf.zip

English

3D PDF

S For support call+1 800 522 6752

3503G2B178RFTD

178 $\Omega,$ Thin Film, Power Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, 2 W, ± 50 ppm/°C, Solder, 3.05 x 1.55 x .43 mm, CGS 3503



3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Aluminium Nitride Thin Film Power Resistor - Type 3503 Series

English