



Magnet coil for contactors 18.5 kW 42 V AC, 50 / 60 Hz, for motor contactors, Size S0, Screw terminal

General technical data	
product brand name	SIRIUS
product designation	Magnet coil
Control circuit	
type of voltage of the control supply voltage	AC
power loss [V·A] of magnet coil at AC typical	10.5 V·A
control supply voltage	
1 at AC — at 50 Hz rated value — at 60 Hz rated value 2 at AC — at 50 Hz rated value — at 60 Hz rated value	42 V 42 V 42 V 42 V
operating range factor control supply voltage rated value of magnet coil at AC	
- at 50 Hz - at 60 Hz	0.8 ... 1.1 0.85 ... 1.1
Certificates/ approvals	
General Product Approval	EMC
Declaration of Conformity	
Shipping Approval	



[Miscellaneous](#)



other

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2926-5AD21>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2926-5AD21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2926-5AD21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2926-5AD21&lang=en

last modified:

4/8/2020 