

## HB-2X2MXS-WWW

~85° wide beam

## SPECIFICATION:

Dimensions	90.0 x 90.0 mm
Height	11.5 mm
Fastening	screw
Ingress protection classes	IP67
ROHS compliant	yes ⓘ


## MATERIALS:

Component	Type	Material	Colour	Finish
HB-2X2MXS-WWW	Multi-lens	Silicone	clear	
STRADA-2X2MXS-FRAME	Holder	PA66	black	

## ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FP15897_HB-2X2MXS-WWW	Multi-lens	240	24	12	12.5
» Box size: 398 x 298 x 265 mm					







See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### OPTICAL RESULTS (MEASURED):


##### LUMILEDS

LED LUXEON M/MX  
FWHM / FWTM 90.0° / 122.0°  
Efficiency 94 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




##### LUMILEDS

LED LUXEON XR-7070 (L224-xxx004MLU010)  
FWHM / FWTM 85.0° / 120.0°  
Efficiency 95 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





##### NICHIA

LED NV4x144A  
FWHM / FWTM 90.0° / 125.0°  
Efficiency 95 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### NICHIA


LED NV9W149AM  
FWHM / FWTM 100.0° / 140.0°  
Efficiency 91 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### OPTICAL RESULTS (MEASURED):



#### SAMSUNG

LED HiLOM SC16 (LH181B)  
 FWHM / FWTM 84.0° / 118.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SCIOLUX

LED XLE-S22C4XD16 (XD16)  
 FWHM / FWTM 87.0° / 124.0°  
 Efficiency 91 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:



#### SEOUL SEMICONDUCTOR

LED WICOP 5050  
 FWHM / FWTM 91.0° / 125.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:






### OPTICAL RESULTS (SIMULATED):




LED Bridgelux SMD 5050  
FWHM / FWTM 79.0° / 115.0°  
Efficiency 94 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### CITIZEN


LED CLU700/701/702/703  
FWHM / FWTM 77.0° / 112.0°  
Efficiency 89 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 434 Typ 2x2MX HV



LED MHB-A/B  
FWHM / FWTM 75.0° / 111.0°  
Efficiency 91 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED XHP70  
FWHM / FWTM 92.0° / 122.0°  
Efficiency 94 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### OPTICAL RESULTS (SIMULATED):




LED XHP70.3 HD  
 FWHM / FWTM 84.0° / 116.0°  
 Efficiency 89 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED LUXEON 7070  
 FWHM / FWTM 74.0° / 108.0°  
 Efficiency 87 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED SFT-40-WCS  
 FWHM / FWTM 62.0° / 102.0°  
 Efficiency 91 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED SFT-70X-WCS  
 FWHM / FWTM 68.0° / 105.0 + 106.0°  
 Efficiency 91 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




### OPTICAL RESULTS (SIMULATED):



LED NFMW48xA  
FWHM / FWTM 73.0° / 107.0°  
Efficiency 91 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSCONIQ C 2424  
FWHM / FWTM 73.0° / 105.0 + 106.0°  
Efficiency 90 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 4  
Light colour White  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)