RLW73A3FR39TE <

CGS | CGS RLW73 TE Internal #: 2-2176548-0 .39 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 1.5 W, ±200 ppm/°C, Solder, Height .024 in [.6 mm], CGS RLW73

View on TE.com >

Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Current Sensing Resistor

Number of Terminations: 2

Package Size Code: 1225

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

Features



Product Type Features

Resistor Type	Current Sensing Resistor
Package Size Code	1225
Element Type	Thick Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Passive Component Tolerance	1 %
Resistance Class	Up to 1kΩ
Resistance Value	.39 Ω
Power Rating	1.5 W
Termination Features	
Number of Terminations	2
Surface Mount Resistor Termination Type	Solder

RLW73A3FR39TE

.39 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 1.5 W, ±200 ppm/°C, Solder, Height .024 in [.6 mm], CGS RLW73



Dimensions

Product Height	.6 mm[.024 in]
Product Length	3.1 mm[.122 in]
Product Width	6.3 mm[.248 in]
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±200 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE

2023 (235) Does not contain REACH SVHC

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Reflow solder capable to 260°C

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

RLW73A3FR39TE

.39 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 1.5 W, ±200 ppm/°C, Solder, Height .024 in [.6 mm], CGS RLW73





Also in the Series | CGS RLW73



Documents

Product Drawings RLW73 A3 1% R39 200ppm 4k RL

English

CAD Files

Customer View Model

ENG_CVM_CVM_2-2176548-0_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-2176548-0_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2-2176548-0_BA.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages CGS Wide Terminal Current Sense Resistor RLW73 English Wide Terminal Current Sense Resistor - Type RLW73 Series English