

2071556-7  ACTIVE

TE Internal #: 2071556-7

Power Relays, Standard, Monostable, DC, 200 mW Coil Power


Rating DC, 720  $\Omega$  Coil Resistance, UL Coil Insulation Class F, 12

VDC Coil Voltage

[View on TE.com >](#)



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: **Standard**

Coil Magnetic System: **Monostable, DC**

Coil Power Rating DC: **200 mW**

Coil Resistance: **720  $\Omega$**

Coil Special Features: **UL Coil Insulation Class F**

## Features

### Product Type Features

Enclosure Type	Sealed
Output Type	AC
Power Relay Type	Standard

### Configuration Features

Output Switching	Random
------------------	--------

### Electrical Characteristics

Insulation Initial Dielectric Between Coil & Contact Class	3500 – 4000 V
Output Current Rating	0 – 10 Arms
Actuating System	DC
Insulation Initial Dielectric Between Open Contacts	750 Vrms
Contact Limiting Short-Time Current	10 A
Coil Power Rating	.2 W
Insulation Creepage Class	7 – 11 mm
Coil Power Rating Class	150 – 200 mW

Insulation Initial Dielectric Between Adjacent Contacts	750 Vrms
Insulation Initial Resistance	1000 M $\Omega$
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
Output Voltage (Max)	250 V
Contact Limiting Making Current	10 A
Insulation Creepage Between Contact & Coil	11 mm[.43 in]
Contact Limiting Continuous Current	10 A
Output Voltage Rating (AC Relays)	0 – 250 Vrms
Output Current (Min)	.1 A
Contact Limiting Breaking Current	10 A
Coil Current	.017 A
Coil Magnetic System	Monostable, DC
Coil Power Rating DC	200 mW
Coil Resistance	720 $\Omega$
Coil Special Features	UL Coil Insulation Class F
Coil Voltage Rating	12 VDC
Contact Switching Load (Min)	100mA @ 5V
Contact Switching Voltage (Max)	250 VAC
Contact Voltage Rating	250 VAC

### Body Features

Product Weight	5.8 g
Case Color	Black

### Contact Features

Contact Plating Material	AgSnO
Switch Arrangement	1 Form A (SPST-NO)
Contact Arrangement	1 Form A (SPST-NO)
Contact Current Class	10 A
Contact Current Rating (Max)	10 A
Contact Material	AgSnOInO
Contact Number of Poles	1
Relay Terminal Type	PCB-THT

### Termination Features

Relay Termination Type	Through Hole
------------------------	--------------

### Mechanical Attachment

Relay Mounting Type	Printed Circuit Board
---------------------	-----------------------

### Dimensions

Length Class (Mechanical)	16 – 20 mm
Height Class (Mechanical)	14 – 15 mm
Insulation Clearance Between Contact & Coil	7 mm[.28 in]
Insulation Clearance Class	7 – 11 mm
Width Class (Mechanical)	10 – 12 mm
Product Width	10.2 mm[.4 in]
Product Length	18.2 mm[.717 in]
Product Height	14.8 mm[.579 in]

### Usage Conditions

Environmental Ambient Temperature (Max)	85 °C[185 °F]
Environmental Ambient Temperature Class	70 – 85 °C
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

### Packaging Features

Packaging Method	Tray/Box
------------------	----------

### Product Compliance

For compliance documentation, visit the product page on [TE.com](http://TE.com)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # 2071556-4  
OJS-SS-112HMF,00000

## Customers Also Bought



TE Part #166292-1  
20DF COSI SOCKET



TE Part #206127-1  
CPC SPECIAL ASSEMBLY SIZE 17



TE Part #4-1879235-5  
SMW5 6R8 1%



TE Part #2-1445100-3  
MICRO MNL HDR ASSY S/ROW LF




TE Part #640387-3  
03P MTA156 HDR ASSY SQ R/A



TE Part #796642-2  
2POS 5.0MM CE VRT HDR,TRM BLK



TE Part #796642-3  
3POS 5.0MM CE VRT HDR,TRM BLK



TE Part #2-84981-0  
1MM FFC SMT H ASSY 20P EMBOSSED



TE Part #2-2176340-9  
CRGQ 0603 47K 5%



TE Part #3-2176325-7  
CRGP 0402 10K 1%

## Documents

**CAD Files**[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_2071556-7\\_A1.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2071556-7\\_A1.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2071556-7\\_A1.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.**Datasheets & Catalog Pages**[OJS\\_10A/16A.STD](#)

English

[OJS Power Miniature PCB 10A / 16A Relays](#)

English

**Product Environmental Compliance**[Product Compliance](#)

English

[Product Compliance](#)

English

**Agency Approvals**[UL](#)

English