



Data

Physical data

Width	1.5 mm / 0.059 inches
Height	22 mm / 0.866 inches
Depth	26 mm / 1.024 inches

Mechanical Data

Design	short
Mounting type	snap-on type

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Flammability class per UL94	V0
Fire load	0.092 MJ
Weight	0.9 g

Commercial data

Product Group	4 (Printed Circuit Connectors)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4017332107150
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Required accessories**End plate**

Feedthrough terminal block		
	Item no.: 226-111 Feedthrough terminal block; Conductor/solder/crimp quick disconnect terminal; Plate thickness: 2.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-111
	Item no.: 226-101 Feedthrough terminal block; Conductor/solder/crimp quick disconnect terminal; Plate thickness: 1.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-101
	Item no.: 226-112 Feedthrough terminal block; Conductor/wire-wrap connection; Plate thickness: 1.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-112
	Item no.: 226-108 Ground conductor feedthrough terminal block; Conductor/solder/crimp quick disconnect terminal; Plate thickness: 1.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; green-yellow	www.wago.com/226-108
	Item no.: 226-107 Ground conductor feedthrough terminal block; Conductor/solder/crimp quick disconnect terminal; Plate thickness: 1.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; green-yellow	www.wago.com/226-107
	Item no.: 226-103 Feedthrough terminal block; Conductor/contact pin; Plate thickness: 2.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-103
	Item no.: 226-114	

Subject to changes. Please also observe the further product documentation!



	Feedthrough terminal block; Conductor/solder/crimp quick disconnect terminal; Plate thickness: 2.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-114
	Item no.: 226-104 Feedthrough terminal block; Conductor/solder/crimp quick disconnect terminal; Plate thickness: 1.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-104
	Item no.: 226-102 Feedthrough terminal block; Conductor/wire-wrap connection; Plate thickness: 1.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-102
	Item no.: 226-113 Feedthrough terminal block; Conductor/contact pin; Plate thickness: 2.5 mm; 4 mm ² ; Pin spacing 6 mm; 1-pole; CAGE CLAMP®; 4,00 mm ² ; gray	www.wago.com/226-113

Downloads

Documentation

Additional Information

	2019 Apr 3	pdf 2.1 MB	Download
--	------------	---------------	----------

CAD/CAE-Data

CAE data

EPLAN Data Portal 226-120	URL	Download
WSCAD Universe 226-120	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 226-120 End plate; for 400 V, cut-out dimensions L1; 1.5 mm thick; gray	URL	Download
---	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.