



Picture differs from the item.

Color coding acc. to DIN VDE 47100		15 poles female Sub-D connector
		Pin number
White	[Color Box]	1
Brown	[Color Box]	2
Green	[Color Box]	3
Yellow	[Color Box]	4
Grey	[Color Box]	5
Pink	[Color Box]	6
Blue	[Color Box]	7
Red	[Color Box]	8
Black	[Color Box]	9
Violet	[Color Box]	10
Grey-Pink	[Color Box]	11
Red-Blue	[Color Box]	12
White-Green	[Color Box]	13
Brown-Green	[Color Box]	14
White-Yellow	[Color Box]	15
Shield	[Color Box]	Connected to Sub-D

## Data Notes

## Note

When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

## Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Subject to changes. Please also observe the further product documentation!

## Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

## Connection 1

Connector	D-subminiature female connector
Pole number 1	15
Connection type 1	System
Wire cross-section	0.25 mm <sup>2</sup>

## Connection 2

Connector 2	open-ended
Connection type 2	open-ended

## Physical data

Cable length	1 m
--------------	-----

## Material data

Weight	156 g
--------	-------

## Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

## Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	box
Country of origin	FR
GTIN	4050821835615
Customs tariff number	85444290900

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastra. 27  
32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169  
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## Downloads

### Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 706-100/615-100

URL

Download

Connection cable; 15-pole; with solder pin; Female connector; open-ended; Length: 1 m; Conductor cross-section: 0.25 mm<sup>2</sup>

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.