

Connection cable; 14-pole; Pluggable connector per DIN 41651; 14-pole; Pluggable connector per DIN 41651; Length: 3 m; Conductor cross-section: 0.14 mm²



Data Notes

Note

When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data

Operating voltage $\leq$ AC/DC 35 V

Subject to changes. Please also observe the further product documentation!

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Current per wire (max.)	1 A
-------------------------	-----

Connection data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1

Connector	Pluggable connector per DIN 41651; female connector
Pole number 1	14
Connection type 1	System
Wire cross-section	0.25 mm ²

Connection 2

Connector 2	Pluggable connector per DIN 41651; female connector
Pole number 2	14
Connection type 2	System

Physical data

Cable length	3 m
--------------	-----

Material data

Weight	234 g
--------	-------

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR
GTIN	4055143976633
Customs tariff number	85444290900

Subject to changes. Please also observe the further product documentation!



Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-150/314-300	URL	Download
Connection cable; 14-pole; Pluggable connector per DIN 41651; 14-pole; Pluggable connector per DIN 41651; Length: 3 m; Conductor cross-section: 0.14 mm²		

Installation Notes

Subject to changes. Please also observe the further product documentation!