

Connection cable; 9-pole; with solder pin; Male and female connector; 9-pole; D-subminiature; Length: 2 m; Conductor cross-section: 0.25 mm²



Data Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Operating voltage $\leq$ AC/DC 35 V

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Current per wire (max.)	2 A
-------------------------	-----

Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1

Connector	D-subminiature male connector
Pole number 1	9
Connection type 1	System
Wire cross-section	0.25 mm ²

Connection 2

Connector 2	D-subminiature female connector
Pole number 2	9
Connection type 2	System

Physical data

Cable length	2 m
--------------	-----

Material data

Weight	272 g
--------	-------

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR
GTIN	4055143977050
Customs tariff number	85444290900

Subject to changes. Please also observe the further product documentation!



Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption
------------------------	------------------------

Downloads
Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-160/509-200	URL	Download
Connection cable; 9-pole; with solder pin; Male and female connector; 9-pole; D-subminiature; Length: 2 m; Conductor cross-section: 0.25 mm²		

Installation Notes

Subject to changes. Please also observe the further product documentation!