



Data sheet | Item number: 756-5312/030-050

Sensor/Actuator cable; M12A plug; angled; 3-pole; Length: 5 m

www.wago.com/756-5312/030-050



Pin 1 ... 4: 0.34 mm²

- 1 ■ brown
- 3 ■ blue
- 4 ■ black

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Data

Technical data

General information

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Insulation resistance	$> 10^9 \Omega$
Contact resistance	10 m Ω
Conductor resistance	$\leq 60 \Omega/\text{km}$
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Drag chain compatible

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	5 m
--------------	-----

Subject to changes. Please also observe the further product documentation!



Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	4.1 ... 4.5 mm

Connector

Connection type	M12 plug - free end
Pole number	3
Cable connection direction to mating direction	90 °
Connector interface coding (cable/adaptor) 1 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	HU
GTIN	4045454942229
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	d2a9d750-5262-4eba-ae1d-f4e7963fa4b8
SCIP notification number (Belgium)	9eab8a5b-52ff-43d8-b123-b215a4b8069c
SCIP notification number (Bulgaria)	7f4760c9-fe19-4761-b234-492435540c19
SCIP notification number (Czech Republic)	cfedc749-dd95-4dba-8a4b-782167bbf683

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



SCIP notification number (Denmark)	9a2828f2-3605-4423-a3b0-977d58d69794
SCIP notification number (Finland)	b0829a01-e16f-4a96-8661-978734fc9c19
SCIP notification number (France)	1c7b5140-0369-4943-b09f-eb69afea945f
SCIP notification number (Germany)	a6179b31-8c03-40c4-9276-a9de1742c4db
SCIP notification number (Hungary)	1f31e8a1-785e-4e38-8c21-e22659b15d76
SCIP notification number (Italy)	e05ab6de-3328-4e4c-b757-73fcc5683316
SCIP notification number (Netherlands)	1330af78-cecb-43f8-b8fc-fee56d6c7e1
SCIP notification number (Poland)	672eb21a-9e83-41ee-80a5-a567d0217ef1
SCIP notification number (Romania)	ec3c0cee-6d3d-4c9a-9195-7084ae01af8b
SCIP notification number (Sweden)	f0b72fe1-9e9a-4a0c-aa16-063c0d0b1c92

Commercial data

eCl@ss 9.0
ETIM 8.0
ETIM 7.0
Customs tariff number

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

Bid Text

756-5312/030-050 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
756-5312/030-050 doc - Datei	2017 Sep 20	doc 26.6 kB	Download

System Description

IP67 Cables and Pluggable Connectors	pdf	Download
--------------------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



130.8 kB

CAD/CAE-Data

CAE data

WSCAD Universe 756-5312/030-050	URL	Download
WSCAD Universe 756-5312/030-050	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5312/030-050	URL	Download
Sensor/Actuator cable; M12A plug; angled; 3-pole; Length: 5 m		

Installation Notes

Subject to changes. Please also observe the further product documentation!