


Item description

- M12 sensor/actuator box, 8-way
- 5-pole (2 signals per contact)

Subject to changes. Please also observe the further product documentation!



- Cable length: 5, 10 and 25 m
- Green LED operating indicator
- Yellow LED status indicator
- incl. markers (10 pcs)
- incl. M12 protective caps (2 pcs)

Data

Technical data

Contact resistance (max.)	0.01 Ω
Supply voltage	10 ... 30 VDC; Rated voltage: 32 V ~ rms
Current carrying capacity (signal connections)	2 A
Current carrying capacity (supply connections)	9 A
Rated value of electrical isolation	500 V
Functionally separated potential groups	Kontakt/Kontakt
Insulation resistance	$>10^9 \Omega$
Signal characteristics	PNP
Indicators	LED (A, B) yellow: Signal status (2 x per contact); LED (U) green: Sensor/actuator box status

Connection data

Connection technology: inputs/outputs	8 x M12 socket; 5-pole; incl. ground
Connection technology: trunk cable	1 x Fixed connecting cable
Length of connection cable	10 m
Strip length	100 mm / 3.94 inches
Wire colors	white, gray/pink, green, red/blue, yellow, white/green, gray, brown /green, pink, white/yellow, red, yellow/brown, black, white/gray, purple, gray/brown, green/yellow, brown, blue
Cable design	Wire cross-section: 0.34 mm ² ; Wire cross-section (2): 1 mm ²

Physical data

Width	60 mm / 2.362 inches
Height	26 mm / 1.024 inches
Depth	152 mm / 5.984 inches

Mechanical Data

Mounting type	Screw mounting
Weight	1613 g

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Material data

Housing material	PA 66 (UL 94 V0); RAL 7035; silicon and halogen free
Halogen-free	Yes
Sheathed cable diameter	9.7 mm
Bending radius	10 x cable diameter (min.) for flexible application
Material properties of the connections	Contact: CuSn, nickel base-coat plating and 0.8 µm gold-plated; Threaded bush: die-cast Zn, nickel-plated; Seal: Viton; 50 mating cycles
Sheath material	PUR
Sheathed cable color	black
Encapsulation	Fully encapsulated with conformal coating (UL 94 V0)

Environmental requirements

Ambient temperature (operation)	-25 ... +80 °C
Ambient (operating) temperature (dynamic)	-5 ... +80 °C
Ambient (operating) temperature (static)	-40 ... +90 °C
Protection type	IP68
Note on protection type	72 h at a depth of 1 m under water per EN 60529 in the fully locked position with its plugs or protective caps
Pollution degree	3 per VDE 0110
Vibration resistance	per IEC 60068-2-6
Shock resistance	per IEC 60068-2-27

Commercial data

eCl@ss 10.0	27-44-01-08
eCl@ss 9.0	27-44-01-08
ETIM 8.0	EC002585
ETIM 7.0	EC002585
Recupel Type	
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4045454028503
Customs tariff number	85366990990

Subject to changes. Please also observe the further product documentation!

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	427ffd3a-66be-4b47-84b4-f50fa769690e
SCIP notification number (Belgium)	2477dc83-50c6-4ddf-b9b6-160c839362c6
SCIP notification number (Bulgaria)	2e238297-4662-460a-bc7a-8386af516888
SCIP notification number (Czech Republic)	b334c42b-bbf1-41ed-8e89-01afcccd3fb8
SCIP notification number (Denmark)	f0283171-95f4-46cd-b42b-9297a7266dab
SCIP notification number (Finland)	08d782bb-1970-44a4-baca-71438edfddb9
SCIP notification number (France)	553b97ad-64f3-4dbf-b9cc-26b2331b19f9
SCIP notification number (Germany)	a3ff771e-b98d-4e5c-94c6-bd242f5dfb48
SCIP notification number (Hungary)	020e11ce-26b4-4ee5-9fa3-778ce5fb437d
SCIP notification number (Italy)	efcd3047-ed45-4394-9122-97b3b7e819f0
SCIP notification number (Netherlands)	baa30e06-c5e6-444d-be57-1c11ff1b9c47
SCIP notification number (Poland)	91038407-a329-4384-8a54-16fc4bb0c22a
SCIP notification number (Romania)	9218ea2b-46b9-42b2-b7f5-8f8163d18667
SCIP notification number (Sweden)	6d09b9c4-27b3-4ec3-9c7c-a9d7516ca2df

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL UL International Germany GmbH (ORDINARY LOCATIONS)	UL 508	E175199 Sec.5

Optional accessories

Cover

	Item no.: 756-8102 M12 protective cap; for unused sockets	www.wago.com/756-8102
---	--	--

Mounting

Intermediate plate

Subject to changes. Please also observe the further product documentation!



Item no.: 757-080
Spacer module for sensor/actuator box; 8-way

www.wago.com/757-080

Marking accessories

Marking strip



Item no.: 757-011
Marker card; not stretchable; snap-on type

www.wago.com/757-011

Marking device



Item no.: 210-110
Fiber-tip pen

www.wago.com/210-110

Downloads

Documentation

Additional Information

Disposal and Recycling	V 1.1.0	pdf	Download
Electrical and electronic equipment, Batteries, Packaging	2022 Aug 18	2.2 MB	

System Description

Sensor/Actuator Boxes – General Product Information	pdf	Download
	438.6 kB	

CAD/CAE-Data

CAD data

2D/3D Models 757-285/000-010	URL	Download
------------------------------	-----	----------

CAE data

EPLAN Data Portal 757-285/000-010	URL	Download
WSCAD Universe 757-285/000-010	URL	Download
ZUKEN Portal 757-285/000-010	URL	Download
WSCAD Universe 757-285/000-010	URL	Download
EPLAN Data Portal 757-285/000-010	URL	Download

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Asset Administration Shell

Asset Administration Shell 757-285/000-010	URL	Download
--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 757-285/000-010	URL	Download
M12 sensor/actuator box; 8-way; 5-pole; 10 m		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.