

Data sheet | Item number: 762-4204/8000-001
Touch Panel 600; 25.7 cm (10.1"); 1280 x 800 pixels; 2 x ETHERNET, 2 x USB,
Audio; Visu Panel




www.wago.com/762-4204/8000-001



Touch Panels 600 Communication Options Overview

	CPU	On Board										Product extensions			
		Modbus RTU (RS-485)	Modbus TCP (Ethernet)	Modbus ASCII	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)	Modbus ASCII (ASCII)
Touch Panels 600 Standard Line	Cortex A9	x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
Touch Panels 600 Advanced Line	Cortex A9	x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
Touch Panels 600 Marine Line	Cortex A9	x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x
		x	x	x	x	x	x	x	x	x	x	x	x	x	x


MC Master, S Slave; *requires an additional license; **requires an additional license (prequalifier: EC 61131 runtime environment; 600 license); ***WagoAppPiModbus Library



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

PIO2 hardware configuration

- 2 x ETHERNET port for connecting to field devices and the engineering tool
- 2 x USB port for optional connection of a USB stick, mouse or keyboard
- Audio interface for connecting a headphone or loudspeaker

Data

Technical data

Display diagonal	25.7 cm (10.1 inches)
Display	Resistive touchscreen
Display colors	16 million colors
Graphics resolution	(1280 x 800) px
Contrast ratio	800:1
Viewing angle (horizontal/vertical)	85° / 85°
Brightness	800 cd/m ²
Visualization	Web server Web-Visu Webserver Web Visu
ETHERNET protocols	DHCP DNS FTP FTPS HTTP

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



	HTTPS SSH
Communication	EtherNet/IP™ adapter (slave), library for <i>e!RUNTIME</i> (prerequisite: <i>e!RUNTIME</i> PLC 600 license) Modbus TCP master/slave (prerequisite: <i>e!RUNTIME</i> PLC 600 license) EtherCAT master, requires an additional license (prerequisite: <i>e!RUNTIME</i> PLC 600 license) BACnet/IP, requires an additional license (prerequisite: <i>e!RUNTIME</i> PLC 600 license)
Operating system	Real-time Linux (with RT-Preempt patch)
Processor	ARM® Cortex® A9 Quadcore 1.0 GHz
Programming environment	<i>e!COCKPIT</i> (based on CODESYS V3)
Main memory (RAM)	2,048 MB
Internal memory (flash)	4096 MB
Program memory	32 MB
Data memory	128 MB
Type of memory card	microSD (max. 2 GB); microSDHC (max. 32 GB)
Indicators	Three-color LED (red, green, blue)
Controls	Resistive touch panel, two capacitive keys, proximity sensor
Supply voltage	24 VDC, SELV (18 ... 31.2 V); with reverse voltage protection
Operating power	11.6 W, without USB load; 16.8 W, with USB load

Connection data

Connection technology: communication/fieldbus	Modbus (TCP): 2 x RJ-45; 2 x USB 2.0 host (type A)
Connection technology: supply	1 x Included female connector (734-103) with three CAGE CLAMP® connections

Physical data

Width	293 mm / 11.535 inches
Height	223 mm / 8.78 inches
Depth	58 mm / 2.283 inches
Panel cutout (W x H)	(278 x 208) mm

Mechanical Data

Weight	1509 g
Front panel	

Subject to changes. Please also observe the further product documentation!



Environmental requirements

Ambient temperature (operation)	-20 ... +55 °C (when mounted vertically; -20 ... +50 °C, other mounting positions)
Ambient temperature (storage)	-20 ... +80 °C
Protection type	IP65
Note on protection type	IP65 (front side); IP20 (rear side), per EN 60529
Relative humidity (without condensation)	90 %
Mounting type	Clamping elements (included) or VESA mount (4 x M4x8)
Fire load	0.003 MJ

Commercial data

ETIM 8.0	EC001414
ETIM 7.0	EC001414
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4055143839402
Customs tariff number	84714100000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC RU C-DE.AM02.B.00087/19
	KC National Radio Research Agency	Article 58-2, Clause 3	MSIP-REM-W43-WBP762
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

Declarations of conformity and manufacturer's declarations

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	DNV DNV Germany GmbH	DNV-CG-0339, Aug. 2021	TAA00001FS

Optional accessories

Software

Software application



Item no.: 2759-208/211-1000
 Library MTP; Single License; Online activation

www.wago.com/2759-208/211-1000

Memory card

Memory card



Item no.: 758-879/000-3102
 Memory Card SD Micro; 2 GByte

www.wago.com/758-879/000-3102



Item no.: 758-879/000-3108
 Memory Card SD Micro; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C

www.wago.com/758-879/000-3108

Mounting

Mounting accessories



Item no.: 762-9001
 elDISPLAY7300T ; Clamping elements (4 pieces)

www.wago.com/762-9001



Item no.: 762-9324
 Flush-Mounted Housing for Touch Panel 600; 25.7 cm (10.1"); 80.0 mm

www.wago.com/762-9324

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Downloads

Documentation

Manual

Product Manual WAGO Touch Panel 600 Standard Line	1.8.0 2023 Dec 4	pdf 4.1 MB	Download
--	---------------------	---------------	----------

Bid Text

762-4204/8000-001 X81 - Datei	2019 Feb 19	xml 5.9 kB	Download
762-4204/8000-001 docx - Datei	2019 Jan 4	docx 22.6 kB	Download
ausschreiben.de 762-4204/8000-001		URL	Download

Tutorial

Establish connection to a controller using SSH In this video we are demonstrating how to establish a SSH connection with a controller using for example PuTTY to be able to work with the LINUX console. Contents: 0:21 Download and install the SSH client; 0:40 Establish the SSH connection; 0:50 Log on to the Controller	1.0 2017 Aug 5	mp4 29.0 MB	Download
---	-------------------	----------------	----------

System Description

Touch Panel 600, system description		pdf 513.5 kB	Download
-------------------------------------	--	-----------------	----------

Additional Information

WAGO OPC UA Server	V 1.1.0 2021 Jan 28	pdf 1.2 MB	Download
--------------------	------------------------	---------------	----------

Engineering-Software

e!COCKPIT

e!COCKPIT Register at no cost and test our engineering software for 30 days.	1.11.2.0 2023 Apr 24	zip 4.1 GB	Download
---	-------------------------	---------------	----------

Configuration and Commissioning Software

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



WAGUpload	1.16.1.0	zip	Download
WAGUpload is a stand-alone PC software for transferring, backing up and restoring PLC applications on WAGO 750 Series controllers.	2022 Feb 2	12.4 MB	

Runtime Software

Firmware

TP 600 Codesys V3.5 Firmware	V 25	zip	Download
TP 600 Codesys V3.5 Firmware	2023 Jul 14	22 B	
Image Update (SD Karte) TP 600	V 22 SP1	zip	Download
WAGO_FW0762-4xxx_V031010_IX22_SP1_I	2022 Dec 14	220.8 MB	
WUP Update (WAGUpload Tool) TP 600	V 22 SP1	zip	Download
WAGO_FW0762-4xxx_V031010_IX22_SP1_W	2022 Dec 14	219.0 MB	

CAD/CAE-Data

CAD data

2D/3D Models 762-4204/8000-001	URL	Download
--------------------------------	-----	----------

CAE data

ZUKEN Portal 762-4204/8000-001	URL	Download
EPLAN Data Portal 762-4204/8000-001	URL	Download

Asset Administration Shell

Asset Administration Shell 762-4204/8000-001	URL	Download
--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 762-4204/8000-001	URL	Download
Touch Panel 600; 25.7 cm (10.1"); 1280 x 800 pixels; 2 x ETHERNET, 2 x USB, Audio; Visu Panel		

Subject to changes. Please also observe the further product documentation!



Installation Notes

Product family

Standard Line

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.