



Color: ■

Item description

Locking system **WINSTA® MIDI**

Implement your installation project with ease: The locking system from the **WINSTA® MIDI** product line is the solution for error-free electrical installation. A comprehensive range of accessories rounds out the **WINSTA®** product line from WAGO. The **WINSTA® MIDI** Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Due to the built-in test slot, it is possible to check connections even when they are plugged in. This saves time, labor, and money.

WINSTA® MIDI solutions for your electrical installation – protected against mismating and maintenance-free

The **WINSTA®** Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismating from WAGO makes the electrical installation of electrical components visibly easier.

■

—
Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

- pre-assembled versions
- fast, secure installation

Data

Connection data

Connection 1

Actuation type	Finger-operated lever
----------------	-----------------------

Mechanical Data

Suitable	for flying leads; manually operated
----------	-------------------------------------

Material data

Note (material data)	Information on material specifications can be found here
----------------------	--

Color	black
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.022 MJ
Weight	0.6 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE

Subject to changes. Please also observe the further product documentation!

GTIN	4017332660907
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

Downloads

Documentation

Bid Text

770-101 X81 - Datei	2019 Feb 19	xml 2.7 kB	Download
770-101 doc - Datei	2015 Mar 11	doc 22.0 kB	Download

CAD/CAE-Data

CAD data

2D/3D Models 770-101	URL	Download
----------------------	-----	----------

CAE data

WSCAD Universe 770-101	URL	Download
------------------------	-----	----------

ZUKEN Portal 770-101

URL	Download
-----	----------

Asset Administration Shell

Asset Administration Shell 770-101	URL	Download
------------------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-101

URL

Download

Locking lever; for flying leads; for manual operation; black

Installation Notes

Product family

WINSTA® MIDI

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastra. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.