



P.C.B LAYOUT

**MATERIALS AND FINISH**

SHELL : STEEL MATERIAL, FRONT SHELL NICKEL FINISHED  
 BACK SHELL TIN FINISHED  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS  
 FILLED, UL 94V-0 RATED, BLACK COLOR  
 CONTACT MATERIAL : BRASS  
 CONTACT FINISH : SELECTIVE GOLD FINISHED  
 RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED

**ELECTRICAL CHARACTERISTICS**

CONTACT CURRENT RATING : 5.0 AMPS  
 DIELECTRIC WITHSTANDING VOLTAGE : 500 V AC MIN.  
 INSULATION RESISTANCE : 1000 MEGOHMS MIN.  
 TEMPERATURE RATING : -40°C ~ +85°C  
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.

**TOLERANCE TABLE**

.0	±0.30
.00	±0.20
.000	±0.05

<b>APPROVED:</b>	<b>DATE:</b>	<b>DATE:</b>	<p>深圳市如科盟实业有限公司          CHANKLEMENT INDUSTRY CO., LTD</p>
<b>CHECKED:</b>	<b>DATE:</b>	<b>DATE:</b>	
<b>DRAWN:</b>	<b>DATE:</b>	<b>DATE:</b>	<p>TITLE: DMS-9P 母头 高胶后轴12.0六角铜柱</p> <p>PART. NO.</p> <p>UNIT mm SCALE free</p> <p>FILE NO. chankt-DMSH-0017 REV. A FILED</p>
ZYJ	2021-12-27		