



Color: —

Data

Physical data

Width	2 mm / 0.079 inches
Height	72.5 mm / 2.854 inches
Depth	35.1 mm / 1.382 inches

Mechanical Data

Mounting type	snap-on type
---------------	--------------

Material data

Note (material data)

Information on material specifications can be found here

Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	VO
Fire load	0.125 MJ
Weight	3.2 g

Subject to changes. Please also observe the further product documentation!

Commercial data

Product Group	22 (TOPJOB S)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4045454654269
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	Railway WAGO GmbH & Co. KG	-	Railway Ready

Required accessories

End plate

Through terminal block	Item no.: 2006-1302  3-conductor through terminal block; 6 mm ² ; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm ² ; orange	www.wago.com/2006-1302
	Item no.: 2006-1304  3-conductor through terminal block; 6 mm ² ; for Ex e II and Ex i applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm ² ; blue	www.wago.com/2006-1304
	Item no.: 2006-1301  3-conductor through terminal block; 6 mm ² ; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm ² ; gray	www.wago.com/2006-1301
	Item no.: 2206-1301  3-conductor through terminal block; with push-button; 6 mm ² ; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm ² ; gray	www.wago.com/2206-1301

Subject to changes. Please also observe the further product documentation!



Item no.: 2206-1304

3-conductor through terminal block; with push-button; 6 mm²; with test port; suitable for Ex i applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; blue

www.wago.com/2206-1304



Item no.: 2006-1305

3-conductor through terminal block; 6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; black

www.wago.com/2006-1305



Item no.: 2006-1301/000-001

3-conductor through terminal block; 6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; green

www.wago.com/2006-1301/000-001



Item no.: 2006-1306

3-conductor through terminal block; 6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; yellow

www.wago.com/2006-1306



Item no.: 2006-1301/000-014

3-conductor through terminal block; 6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; brown

www.wago.com/2006-1301/000-014



Item no.: 2206-1305

3-conductor through terminal block; with push-button; 6 mm²; with test port; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; black

www.wago.com/2206-1305



Item no.: 2006-1303

3-conductor through terminal block; 6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; red

www.wago.com/2006-1303



Item no.: 2206-1303

3-conductor through terminal block; with push-button; 6 mm²; with test port; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; red

www.wago.com/2206-1303

Ground terminal block



Item no.: 2006-1307

3-conductor ground terminal block; 6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; green-yellow

www.wago.com/2006-1307



Item no.: 2206-1307

3-conductor ground terminal block; with push-button; 6 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; green-yellow

www.wago.com/2206-1307

Downloads

Documentation

Bid Text

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

2006-1393 X81 - Datei	2019 Feb 19	xml 2.6 kB	Download
2006-1393 doc - Datei	2017 Apr 28	doc 24.1 kB	Download
Additional Information			
		pdf 2.3 MB	Download

CAD/CAE-Data

CAD data

2D/3D Models 2006-1393	URL	Download
CAE data		
EPLAN Data Portal 2006-1393	URL	Download
WSCAD Universe 2006-1393	URL	Download
ZUKEN Portal 2006-1393	URL	Download

Asset Administration Shell

Asset Administration Shell 2006-1393	URL	Download
--------------------------------------	-----	--------------------------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2006-1393 Seperator plate; 2 mm thick; oversized; gray	URL	Download
--	-----	--------------------------

Installation Notes

Subject to changes. Please also observe the further product documentation!

Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.