

Data  
Physical data

Width	0.8 mm / 0.031 inches
Height	61.5 mm / 2.421 inches
Depth	33 mm / 1.299 inches

Mechanical Data

Mounting type	snap-on type
---------------	--------------

Material data

Note (material data)	Information on material specifications can be found here
Color	orange
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Weight	1.5 g

Subject to changes. Please also observe the further product documentation!

## Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

## Commercial data






eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4055143745352
Customs tariff number	85389099990

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Required accessories

### End plate

Through terminal block		
	<b>Item no.: 2102-1201</b> 2-conductor through terminal block; with lever and Push-in CAGE CLAMP®; 2.5 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; gray	<a href="http://www.wago.com/2102-1201">www.wago.com/2102-1201</a>
	<b>Item no.: 2102-1204</b> 2-conductor through terminal block; with lever and Push-in CAGE CLAMP®; 2.5 mm²; with test port; suitable for Ex i applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; blue	<a href="http://www.wago.com/2102-1204">www.wago.com/2102-1204</a>
	<b>Item no.: 2102-5201</b> 2-conductor through terminal block; with lever and push-button; 2.5 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; gray	<a href="http://www.wago.com/2102-5201">www.wago.com/2102-5201</a>
	<b>Item no.: 2102-5204</b> 2-conductor through terminal block; with lever and push-button; 2.5 mm²; with test port; suitable for Ex i applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; blue	<a href="http://www.wago.com/2102-5204">www.wago.com/2102-5204</a>
Ground terminal block		
	<b>Item no.: 2102-1207</b> 2-conductor ground terminal block; with lever and Push-in CAGE CLAMP®; 2.5 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; green-yellow	<a href="http://www.wago.com/2102-1207">www.wago.com/2102-1207</a>

**Item no.: 2102-5207**

Subject to changes. Please also observe the further product documentation!



2-conductor ground terminal block; with lever and push-button; 2.5 mm<sup>2</sup>; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; green-yellow

[www.wago.com/2102-5207](http://www.wago.com/2102-5207)

## Downloads

### Documentation

#### Bid Text

2102-1292 X81 - Datei	2019 Feb 19	xml 2.6 kB	Download
--------------------------	-------------	---------------	----------

2102-1292 docx - Datei	2018 Aug 8	docx 14.5 kB	Download
---------------------------	------------	-----------------	----------

#### Additional Information

		pdf 2.3 MB	Download
--	--	---------------	----------

## CAD/CAE-Data

### CAD data

2D/3D Models 2102-1292	URL	Download
------------------------	-----	----------

### CAE data

EPLAN Data Portal 2102-1292	URL	Download
-----------------------------	-----	----------

ZUKEN Portal 2102-1292	URL	Download
------------------------	-----	----------

### Asset Administration Shell

Asset Administration Shell 2102-1292	URL	Download
--------------------------------------	-----	----------

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 2102-1292 End and intermediate plate; 0.8 mm thick; orange	URL	Download
--	-----	----------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Installation Notes

## Product family

### TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.