



Color: ■

Data

Physical data

Width	1 mm / 0.039 inches
Height	69.5 mm / 2.736 inches
Depth	30.5 mm / 1.201 inches

Mechanical Data

Mounting type	snap-on type
---------------	--------------

Material data

Note (material data)

Information on material specifications can be found here

Color	orange
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	VO
Fire load	0.066 MJ
Weight	2.3 g

Subject to changes. Please also observe the further product documentation!

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Country of origin	DE
GTIN	4055143975384
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
	UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Required accessories

End plate

Through terminal block		Item no.: 2104-1201 2-conductor through terminal block; with lever and Push-in CAGE CLAMP®; 4 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 4,00 mm²; gray	www.wago.com/2104-1201
		Item no.: 2104-1204 2-conductor through terminal block; with lever and Push-in CAGE CLAMP®; 4 mm²; with test port; suitable for Ex i applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 4,00 mm²; blue	www.wago.com/2104-1204

Subject to changes. Please also observe the further product documentation!



Item no.: 2104-5201

2-conductor through terminal block; with lever and push-button; 4 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 4,00 mm²; gray

www.wago.com/2104-5201



Item no.: 2104-5204

2-conductor through terminal block; with lever and push-button; 4 mm²; with test port; suitable for Ex i applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 4,00 mm²; blue

www.wago.com/2104-5204

Ground terminal block



Item no.: 2104-1207

2-conductor ground terminal block; with lever and Push-in CAGE CLAMP®; 4 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 4,00 mm²; green-yellow

www.wago.com/2104-1207



Item no.: 2104-5207

2-conductor ground terminal block; with lever and push-button; 4 mm²; with test port; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 4,00 mm²; green-yellow

www.wago.com/2104-5207

Downloads

Documentation

Bid Text

2104-1292	docx	Download
doc - Datei	20.8 kB	

2104-1292	xml	Download
X81 - Datei	3.0 kB	

Additional Information

	pdf	Download
	2.3 MB	

CAD/CAE-Data

CAD data

2D/3D Models 2104-1292	URL	Download
------------------------	-----	--------------------------

CAE data

ZUKEN Portal 2104-1292	URL	Download
------------------------	-----	--------------------------

EPLAN Data Portal 2104-1292	URL	Download
-----------------------------	-----	--------------------------

Asset Administration Shell

Asset Administration Shell 2104-1292	URL	Download
--------------------------------------	-----	--------------------------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27
32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2104-1292

URL

Download

End and intermediate plate; 1 mm thick; orange

Installation Notes

Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.