




Part Number : 350369802  
Product Description : .250mm Fuse Terminal,  
0.85mm<sup>2</sup> - 2.50mm<sup>2</sup>  
Series Number : 35036  
Status : Obsolete  
Product Category : Crimp Terminals



Documents & Resources

Product Environment Compliance

Compliance

|                    |                                                |
|--------------------|------------------------------------------------|
| GADSL/IMDS         | Duty-To-Declare                                |
| China RoHS         |                                                |
| EU ELV             | Compliant per 2000/53/EC                       |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                 |
| REACH SVHC         | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS            | Compliant per EU 2015/863                      |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

|        |          |
|--------|----------|
| Status | Obsolete |
|--------|----------|

|              |                                                                 |
|--------------|-----------------------------------------------------------------|
| Category     | Crimp Terminals                                                 |
| Series       | 35036                                                           |
| Description  | .250mm Fuse Terminal, 0.85mm <sup>2</sup> - 2.50mm <sup>2</sup> |
| Application  | Power, Wire-to-Component                                        |
| Comments     | Box Type                                                        |
| Product Name | N/A                                                             |
| UPC          | 800753238848                                                    |

## Electrical

|                               |              |
|-------------------------------|--------------|
| Current - Maximum per Contact | 10.0A, 18.0A |
| Voltage - Maximum             | 3V           |

## Physical

|                                |                      |
|--------------------------------|----------------------|
| Durability (mating cycles max) | 10                   |
| Gender                         | Female               |
| Material - Metal               | Brass                |
| Material - Plating Mating      | Tin                  |
| Material - Plating Termination | Tin                  |
| Net Weight                     | 0.760/g              |
| Packaging Type                 | Reel                 |
| Termination Interface Style    | Crimp or Compression |
| Wire Insulation Diameter       | 2.20-3.10mm          |
| Wire Size (AWG)                | 14, 16, 18           |
| Wire Size mm <sup>2</sup>      | 0.85-2.50            |