




**Part Number :** [436401101](#)  
**Product Description :** Micro-Fit 3.0 Plug  
Housing, Single Row, 11 Circuits, UL 94V-0,  
Low-Halogen, Black  
**Series Number :** 43640  
**Status :** Active  
**Product Category :** Connector Housings



## Documents & Resources


**Drawings**  
[Drawing 436401101\\_sd.pdf](#)

**3D Models and Design Files**  
[3D Model 436401101\\_stp.zip](#)

**Specifications**  
[Packaging Specification PK-43640-003-001.pdf](#)  
[Product Specification 436500001-PS-JA-000.pdf](#)  
[Product Specification 436500001-PS-KO-000.pdf](#)  
[Product Specification 436500001-PS-SP-000.pdf](#)  
[Product Specification PS-43650-001.pdf](#)  
[Test Summary 430450005-TS-000.pdf](#)  
[Test Summary TS-43045-001-001.pdf](#)  
[Test Summary TS-43045-002-001.pdf](#)  
[Test Summary TS-43045-003-001.pdf](#)  
[Test Summary TS-46235-001-001.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Connector Housings
Series	43640
Description	Micro-Fit 3.0 Plug Housing, Single Row, 11 Circuits, UL 94V-0, Low-Halogen, Black
Application	Power, Wire-to-Wire
Product Family	Micro-Fit Connector System
Product Name	Micro-Fit 3.0
UPC	800754712569

### Agency

CSA	LR19980
UL	E29179

### Physical

Circuits (maximum)	11
Color - Resin	Black
Flammability	94V-0
Gender	Plug
Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes

Material - Resin	Nylon
Net Weight	1.786/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	3.00mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +105°C

#### Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

---

#### Mates With / Use With

##### Mates with Part(s)

Description	Part Number
Micro-Fit 3.0 Single Row Receptacle Housings	<u>43645</u>

##### Use with Part(s)

Description	Part Number
Micro-Fit Male Crimp Terminals	<u>43031</u>
Pre-Crimped Lead Micro-Fit 3.0 Male-to-Micro-Fit 3.0 Male	<u>214762</u>
Pre-Crimped Lead Micro-Fit 3.0 Male-to-Pigtail	<u>214763</u>