






Color: ■■■



Dimensions in mm


Cutting mark for separating the retaining clip and its snap-in mounting foot

Adapters with snap-in mounting foot cut off assembled on both ends (7 to 9 poles)



For lengths longer than 7 poles, the snap-in mounting foot with retaining clip should be cut off (see example below).

Adapters with snap-in mounting foot cut off in center position (10 to 15 poles)



Adapters A: Snap-in mounting foot with retaining clip cut off

Adapters B: Standard version

Data

Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Ratings per IEC/EN

| | |
|-------------------------------|--|
| Ratings per | IEC/EN 60664-1 |
| Rated voltage (III/2) | 320 V |
| Rated impulse voltage (III/2) | 4 kV |
| Rated current | 6 A |
| Legend (ratings) | (III / 2) \triangleq Overvoltage category III / Pollution degree 2 |

Connection data

Connection 1

| | |
|-------------|---|
| Pole number | 1 |
|-------------|---|

Physical data

| | |
|-------------|------------------------|
| Pin spacing | 5 mm / 0.197 inches |
| Width | 5 mm / 0.197 inches |
| Height | 21.5 mm / 0.846 inches |
| Depth | 19.5 mm / 0.768 inches |

Mechanical Data

| | |
|----------|--|
| Suitable | for PCB terminal blocks (255, 256, 257 Series); with socket for 2 mm and 2.3 mm Ø test plugs |
|----------|--|

Material data

| | |
|-----------------------------|--|
| Note (material data) | Information on material specifications can be found here |
| Color | gray |
| Material group | I |
| Insulation material | Polyamide (PA66) |
| Flammability class per UL94 | V0 |
| Fire load | 0.024 MJ |
| Weight | 1.3 g |

Environmental requirements

| | |
|-------------------------|-----------------|
| Limit temperature range | -60 ... +105 °C |
|-------------------------|-----------------|

Subject to changes. Please also observe the further product documentation!

Commercial data

| | |
|-----------------------|--------------------------------|
| Product Group | 2 (Terminal Block Accessories) |
| eCl@ss 10.0 | 27-14-11-48 |
| eCl@ss 9.0 | 27-14-11-48 |
| ETIM 8.0 | EC002255 |
| ETIM 7.0 | EC002255 |
| PU (SPU) | 100 (25) pcs |
| Packaging type | box |
| Country of origin | CH |
| GTIN | 4045454306816 |
| Customs tariff number | 85366990990 |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Downloads

Documentation

Additional Information

2019 Apr 3

pdf
2.1 MB[Download](#)

CAD/CAE-Data

CAD data

| | | |
|----------------------|-----|--------------------------|
| 2D/3D Models 249-110 | URL | Download |
|----------------------|-----|--------------------------|

CAE data

| | | |
|---------------------------|-----|--------------------------|
| EPLAN Data Portal 249-110 | URL | Download |
|---------------------------|-----|--------------------------|

ZUKEN Portal 249-110

| | | |
|----------------------|-----|--------------------------|
| ZUKEN Portal 249-110 | URL | Download |
|----------------------|-----|--------------------------|

Asset Administration Shell

| | | |
|------------------------------------|-----|--------------------------|
| Asset Administration Shell 249-110 | URL | Download |
|------------------------------------|-----|--------------------------|

Environmental Product Compliance

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastra. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Compliance Search

Environmental Product Compliance 249-110


URL

Download

Test plug adapter; suitable for 255, 256, 257 Series PCB terminal blocks; 1-pole; Pin spacing 5 mm / 0.197 in; gray


Installation Notes

Installation



Assembling a multipole test plug adapter.

Installation



Inserting a test plug adapter into a terminal strip.

Testing

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastra. 27


32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com


Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Testing wired terminal blocks.

Application



9-pole test plug adapter – external snap-in
mounting feet with retaining clips cut off

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.