



Data
Physical data

Pin spacing	5/5.08 mm / 0.197/0.2 inches
Width	5.08 mm / 0.2 inches
Height	13.6 mm / 0.535 inches
Depth	14.2 mm / 0.559 inches

Mechanical Data

Application	extends pin spacing
Mounting type	snap-on type

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.016 MJ

Subject to changes. Please also observe the further product documentation!



Weight	0.5 g
--------	-------

Commercial data

Product Group	4 (Printed Circuit Connectors)
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	500 (100) pcs
Packaging type	box
Country of origin	CH
GTIN	4017332445344
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads**Documentation****Additional Information**

	2019 Apr 3	pdf 2.1 MB	Download
--	------------	---------------	----------

CAD/CAE-Data**CAE data**

EPLAN Data Portal 257-801	URL	Download
ZUKEN Portal 257-801	URL	Download

CAD data

2D/3D Models 257-801	URL	Download
----------------------	-----	----------

Asset Administration Shell

Asset Administration Shell 257-801	URL	Download
------------------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 257-801	URL	Download
Spacer; for doubling the pin spacing; 5/5.08 mm thick; gray		

Installation Notes

Subject to changes. Please also observe the further product documentation!