

Data sheet | Item number: 285-169
Finger guard; touchproof cover protects unused conductor entries and jumper slots; for 95 mm² high-current tbs; yellow

www.wago.com/285-169



Data
Material data

Note (material data)

Information on material specifications can be found [here](#)

Color	yellow
Material group	I
Insulation material	Polyamide (PA66)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Flammability class per UL94	V0
Fire load	0.08 MJ
Weight	2.7 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	25 pcs
Packaging type	box
Country of origin	DE
GTIN	4017332028691
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

285-169	2019 Feb 19	xml	Download
X81 - Datei		2.7 kB	

285-169	2017 Feb 27	doc	Download
doc - Datei		23.0 kB	

Additional Information

		pdf	Download
		2.3 MB	

Subject to changes. Please also observe the further product documentation!



CAD/CAE-Data

CAD data

2D/3D Models 285-169	URL	Download
----------------------	-----	----------

CAE data

WSCAD Universe 285-169	URL	Download
ZUKEN Portal 285-169	URL	Download
EPLAN Data Portal 285-169	URL	Download

Asset Administration Shell

Asset Administration Shell 285-169	URL	Download
------------------------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 285-169	URL	Download
Finger guard; touchproof cover protects unused conductor entries and jumper slots; for 95 mm² high-current tbs; yellow		

Installation Notes

Cover



Yellow, detachable finger guards provide touch-proof safety by shielding jumper contact slots and/or unused conductor entries.

Subject to changes. Please also observe the further product documentation!