







Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Item description

This potential multiplication module provides 24 V to the inputs in combination with the 8-channel input module (750-430/-431).

This eliminates the need for additional DIN-rail-mount terminal blocks.

The 24 V supply and 0 V potential are derived from the internal power jumper contacts of an adjacent upstream I/O module. A connection of the potentials to the downstream I/O modules is made automatically via the power jumper contacts when snapping the I/O modules together. The 24 V power is provided to all eight field side CAGE CLAMP® connections and the 0 V potential passed through without being used by the module.

## Data Notes

### Note

Pluggable connectors and coding fingers (753 Series) are not included.

Subject to changes. Please also observe the further product documentation!



## Technical data

|                                                   |                                                                                                                                                      |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Signal type                                       | Voltage                                                                                                                                              |
| Signal type (voltage)                             | 24 VDC                                                                                                                                               |
| Supply voltage (system)                           | 5 VDC; via data contacts                                                                                                                             |
| Supply voltage (field)                            | 24 VDC (-25 ... +30 %); via power jumper contacts (power supply via blade contact; transmission (supply voltage field side only) via spring contact) |
| Number of incoming power jumper contacts          | 2                                                                                                                                                    |
| Number of outgoing power jumper contacts          | 2                                                                                                                                                    |
| Current carrying capacity (power jumper contacts) | 10 A                                                                                                                                                 |

## Connection data

|                         |                                              |
|-------------------------|----------------------------------------------|
| Connection type 1       | Field supply                                 |
| Solid conductor         | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Fine-stranded conductor | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Strip length            | 9 ... 10 mm / 0.35 ... 0.39 inches           |

## Physical data

|                                   |                        |
|-----------------------------------|------------------------|
| Width                             | 12 mm / 0.472 inches   |
| Height                            | 100 mm / 3.937 inches  |
| Depth                             | 69.8 mm / 2.748 inches |
| Depth from upper-edge of DIN-rail | 62.6 mm / 2.465 inches |

## Mechanical Data

|                     |             |
|---------------------|-------------|
| Mounting type       | DIN-35 rail |
| Pluggable connector | Pluggable   |

## Material data

|                    |                              |
|--------------------|------------------------------|
| Color              | light gray                   |
| Housing material   | Polycarbonate; polyamide 6.6 |
| Fire load          | 0.869 MJ                     |
| Weight             | 36.5 g                       |
| Conformity marking | CE                           |

Subject to changes. Please also observe the further product documentation!



## Environmental requirements

|                                                                                    |                                       |
|------------------------------------------------------------------------------------|---------------------------------------|
| Ambient temperature (operation)                                                    | 0 ... +55 °C                          |
| Ambient temperature (storage)                                                      | -40 ... +85 °C                        |
| Protection type                                                                    | IP20                                  |
| Pollution degree                                                                   | 2 per IEC 61131-2                     |
| Operating altitude                                                                 | 0 ... 2000 m / 0 ... 6562 ft          |
| Mounting position                                                                  | horizontal (standing/lying); vertical |
| Relative humidity (without condensation)                                           | 95 %                                  |
| Vibration resistance                                                               | 4g per IEC 60068-2-6                  |
| Shock resistance                                                                   | 15g per IEC 60068-2-27                |
| EMC immunity to interference                                                       | per EN 61000-6-2, marine applications |
| EMC emission of interference                                                       | per EN 61000-6-4, marine applications |
| Exposure to pollutants                                                             | Per IEC 60068-2-42 and IEC 60068-2-43 |
| Permissible H <sub>2</sub> S contaminant concentration at a relative humidity 75 % | 10 ppm                                |
| Permissible SO <sub>2</sub> contaminant concentration at a relative humidity 75 %  | 25 ppm                                |

## Commercial data

|                       |                 |
|-----------------------|-----------------|
| Product Group         | 15 (I/O System) |
| eCl@ss 10.0           | 27-24-26-10     |
| eCl@ss 9.0            | 27-24-26-10     |
| ETIM 8.0              | EC001600        |
| ETIM 7.0              | EC001600        |
| Recupel Type          |                 |
| PU (SPU)              | 1 pcs           |
| Packaging type        | box             |
| Country of origin     | DE              |
| GTIN                  | 4050821867616   |
| Customs tariff number | 85389091890     |

## Environmental Product Compliance

|                        |                         |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## Approvals / Certificates

### General approvals

| Logo                                                                             | Approval                                      | Additional Approval Text | Certificate name                    |
|----------------------------------------------------------------------------------|-----------------------------------------------|--------------------------|-------------------------------------|
|  | <b>EAC</b><br>Brjansker Zertifizierungsstelle | TP TC 020/2011           | EAC RU C-DE.AM02.<br>B.00087<br>/19 |
|   | <b>KC</b><br>National Radio Research Agency   | Article 58-2, Clause 3   | MSIP-REM-W43-FSC750                 |

### Declarations of conformity and manufacturer's declarations

| Logo                                                                             | Approval                                                  | Additional Approval Text | Certificate name |
|----------------------------------------------------------------------------------|-----------------------------------------------------------|--------------------------|------------------|
|  | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

### Approvals for marine applications

| Logo                                                                                | Approval                                                     | Additional Approval Text | Certificate name  |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------|--------------------------|-------------------|
|  | <b>BSH</b><br>Bundesamt fuer Seeschifffahrt und Hydrographie | -                        | 1104              |
|  | <b>BV</b><br>Bureau Veritas S.A.                             | -                        | 30389/C0 BV       |
|   | <b>DNV</b><br>DNV GL SE                                      | DNV-CG-0339, Aug. 2021   | TAA0000194        |
|   | <b>KR</b><br>Korean Register of Shipping                     | -                        | KR HMB05880-AC001 |
|  | <b>LR</b><br>Lloyds Register EMEA                            | -                        | LR22180952TA      |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)


Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



RINA  
RINA Germany GmbH

ELE343521XG001

## Approvals for hazardous areas

| Logo                                                                               | Approval                                                      | Additional Approval Text | Certificate name                                     |
|------------------------------------------------------------------------------------|---------------------------------------------------------------|--------------------------|------------------------------------------------------|
|    | ATEX<br>TUEV Nord Cert GmbH                                   | EN 60079-0               | TUEV14ATEX148929X (II 3 G<br>Ex ec IIC T4 Gc)        |
|    | CCCEX<br>CQST/CNEX                                            | CNCA-C23-01              | 2020312310000213 (Ex ec IIC<br>T4 Gc)                |
|    | EAC<br>Brjansker Zertifizierungsstelle                        | TP TC 012/2011           | EAC RU C-DE.AM02.B.00163<br>/19 (2Ex nA IIC T4 Gc X) |
|    | IECEX<br>TUEV Nord Cert GmbH                                  | IEC 60079-0              | IECEX TUN 14.0035 X (Ex ec<br>IIC T4 Gc)             |
|  | INMETRO<br>TÜV Rheinland do Brasil Ltda.                      | IEC 60079-0              | BR-Ex_TÜV 12.1297 X                                  |
|  | UKEx<br>WAGO GmbH & Co. KG                                    | EN 60079-0               | UKCA_WAGO22UKEX003X_ec                               |
|  | UL<br>Underwriters Laboratories Inc. (HAZARDOUS<br>LOCATIONS) | UL 121201                | E198726 Sec.1                                        |

## Required accessories

## Pluggable connector

Male connector/plug



Item no.: 753-110  
Plug

[www.wago.com/753-110](http://www.wago.com/753-110)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## Optional accessories

## Marking accessories

|                                                                                    |                                                                                                                                                   |                                                                                  |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| Marker carrier                                                                     |                                                                                                                                                   |                                                                                  |
|     | <b>Item no.: 750-103</b><br>Group marker carrier                                                                                                  | <a href="http://www.wago.com/750-103">www.wago.com/750-103</a>                   |
| Marker                                                                             |                                                                                                                                                   |                                                                                  |
|    | <b>Item no.: 2009-145/000-006</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue   | <a href="http://www.wago.com/2009-145/000-006">www.wago.com/2009-145/000-006</a> |
|    | <b>Item no.: 2009-145</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white          | <a href="http://www.wago.com/2009-145">www.wago.com/2009-145</a>                 |
|    | <b>Item no.: 2009-145/000-002</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow | <a href="http://www.wago.com/2009-145/000-002">www.wago.com/2009-145/000-002</a> |
|    | <b>Item no.: 2009-145/000-007</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray   | <a href="http://www.wago.com/2009-145/000-007">www.wago.com/2009-145/000-007</a> |
|   | <b>Item no.: 2009-145/000-005</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red    | <a href="http://www.wago.com/2009-145/000-005">www.wago.com/2009-145/000-005</a> |
|  | <b>Item no.: 2009-145/000-012</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange | <a href="http://www.wago.com/2009-145/000-012">www.wago.com/2009-145/000-012</a> |
|  | <b>Item no.: 2009-145/000-023</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green  | <a href="http://www.wago.com/2009-145/000-023">www.wago.com/2009-145/000-023</a> |
|  | <b>Item no.: 2009-145/000-024</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet | <a href="http://www.wago.com/2009-145/000-024">www.wago.com/2009-145/000-024</a> |
|  | <b>Item no.: 248-501/000-006</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue                                    | <a href="http://www.wago.com/248-501/000-006">www.wago.com/248-501/000-006</a>   |
|  | <b>Item no.: 248-501/000-007</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray                                    | <a href="http://www.wago.com/248-501/000-007">www.wago.com/248-501/000-007</a>   |

Subject to changes. Please also observe the further product documentation!

**Item no.: 248-501/000-002**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow

[www.wago.com/248-501/000-002](http://www.wago.com/248-501/000-002)**Item no.: 248-501/000-012**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange

[www.wago.com/248-501/000-012](http://www.wago.com/248-501/000-012)**Item no.: 248-501**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

[www.wago.com/248-501](http://www.wago.com/248-501)**Item no.: 248-501/000-017**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green

[www.wago.com/248-501/000-017](http://www.wago.com/248-501/000-017)**Item no.: 248-501/000-005**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red

[www.wago.com/248-501/000-005](http://www.wago.com/248-501/000-005)**Item no.: 248-501/000-024**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet

[www.wago.com/248-501/000-024](http://www.wago.com/248-501/000-024)**Item no.: 248-501/000-023**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green

[www.wago.com/248-501/000-023](http://www.wago.com/248-501/000-023)**Item no.: 750-100**

Marker card; as a DIN A4 sheet; plain

[www.wago.com/750-100](http://www.wago.com/750-100)

## Group marker carrier

**Item no.: 750-106**

Group marker carrier

[www.wago.com/750-106](http://www.wago.com/750-106)**Supply module**

## Supply module

**Item no.: 750-601**

Power Supply; 24 VDC; fuse holder

[www.wago.com/750-601](http://www.wago.com/750-601)**Item no.: 750-610**

Power Supply; 24 VDC; fuse holder; Diagnostics

[www.wago.com/750-610](http://www.wago.com/750-610)**Item no.: 750-602**

Power Supply; 24 VDC

[www.wago.com/750-602](http://www.wago.com/750-602)**Item no.: 750-612**[www.wago.com/750-612](http://www.wago.com/750-612)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Power Supply; 0 ... 230 V AC/DC

**Item no.: 753-612**

Power Supply; 0 ... 230 V AC/DC

[www.wago.com/753-612](http://www.wago.com/753-612)**Item no.: 753-602**

Power Supply; 24 VDC

[www.wago.com/753-602](http://www.wago.com/753-602)**Carrier rail**

## Mounting accessories

**Item no.: 210-197**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored

[www.wago.com/210-197](http://www.wago.com/210-197)**Item no.: 210-198**

Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored

[www.wago.com/210-198](http://www.wago.com/210-198)**Item no.: 210-504**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored

[www.wago.com/210-504](http://www.wago.com/210-504)**Item no.: 210-505**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored

[www.wago.com/210-505](http://www.wago.com/210-505)**Item no.: 210-506**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored

[www.wago.com/210-506](http://www.wago.com/210-506)**Item no.: 210-508**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored

[www.wago.com/210-508](http://www.wago.com/210-508)**Item no.: 210-113**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

[www.wago.com/210-113](http://www.wago.com/210-113)**Item no.: 210-118**

Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

[www.wago.com/210-118](http://www.wago.com/210-118)**Item no.: 210-112**


Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored

[www.wago.com/210-112](http://www.wago.com/210-112)**Item no.: 210-114**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-114](http://www.wago.com/210-114)**Item no.: 210-115**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored

[www.wago.com/210-115](http://www.wago.com/210-115)**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-196](http://www.wago.com/210-196)**Shield termination**

## Shield clamping saddles

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

|                                                                                    |                                                                                                                                         |                                                                                |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
|     | <b>Item no.: 790-116</b><br>Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm                           | <a href="http://www.wago.com/790-116">www.wago.com/790-116</a>                 |
|     | <b>Item no.: 790-124</b><br>Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm                           | <a href="http://www.wago.com/790-124">www.wago.com/790-124</a>                 |
|     | <b>Item no.: 790-108</b><br>Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm                            | <a href="http://www.wago.com/790-108">www.wago.com/790-108</a>                 |
|     | <b>Item no.: 790-140</b><br>Shield clamping saddle; diameter of compatible conductor                                                    | <a href="http://www.wago.com/790-140">www.wago.com/790-140</a>                 |
|     | <b>Item no.: 790-216</b><br>Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm                                                           | <a href="http://www.wago.com/790-216">www.wago.com/790-216</a>                 |
|     | <b>Item no.: 790-220</b><br>Shield clamping saddle; 30 mm wide; 6 ... 20 mm                                                             | <a href="http://www.wago.com/790-220">www.wago.com/790-220</a>                 |
|     | <b>Item no.: 790-208</b><br>Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm                                                            | <a href="http://www.wago.com/790-208">www.wago.com/790-208</a>                 |
| <b>System housing</b>                                                              |                                                                                                                                         |                                                                                |
| System enclosure                                                                   |                                                                                                                                         |                                                                                |
|    | <b>Item no.: 850-814/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate                | <a href="http://www.wago.com/850-814/002-000">www.wago.com/850-814/002-000</a> |
|   | <b>Item no.: 850-815/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate                | <a href="http://www.wago.com/850-815/002-000">www.wago.com/850-815/002-000</a> |
|  | <b>Item no.: 850-816/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate                | <a href="http://www.wago.com/850-816/002-000">www.wago.com/850-816/002-000</a> |
|  | <b>Item no.: 850-817/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate                | <a href="http://www.wago.com/850-817/002-000">www.wago.com/850-817/002-000</a> |
|  | <b>Item no.: 850-825</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20                              | <a href="http://www.wago.com/850-825">www.wago.com/850-825</a>                 |
|  | <b>Item no.: 850-826</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip         | <a href="http://www.wago.com/850-826">www.wago.com/850-826</a>                 |
|  | <b>Item no.: 850-827</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip         | <a href="http://www.wago.com/850-827">www.wago.com/850-827</a>                 |
|  | <b>Item no.: 850-827/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip | <a href="http://www.wago.com/850-827/002-000">www.wago.com/850-827/002-000</a> |

Subject to changes. Please also observe the further product documentation!

**Item no.: 850-826/002-000**

IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip

[www.wago.com/850-826/002-000](http://www.wago.com/850-826/002-000)**Item no.: 850-828/002-000**

IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip

[www.wago.com/850-828/002-000](http://www.wago.com/850-828/002-000)**Item no.: 850-828**

IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip

[www.wago.com/850-828](http://www.wago.com/850-828)**Item no.: 850-834**

IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20

[www.wago.com/850-834](http://www.wago.com/850-834)**Item no.: 850-835**

IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip

[www.wago.com/850-835](http://www.wago.com/850-835)**Item no.: 850-836**

IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip

[www.wago.com/850-836](http://www.wago.com/850-836)**Pluggable connector****Coding****Item no.: 753-150**

753 Series coding elements

[www.wago.com/753-150](http://www.wago.com/753-150)**Downloads****Documentation****Manual**

|                                                                              |                        |               |          |
|------------------------------------------------------------------------------|------------------------|---------------|----------|
| System Manual WAGO I/O System 750/753<br>Decentralized Automation Technology | V 3.3.3<br>2023 Aug 29 | pdf<br>8.7 MB | Download |
|------------------------------------------------------------------------------|------------------------|---------------|----------|

|                                                    |         |               |          |
|----------------------------------------------------|---------|---------------|----------|
| Product Manual Field-side connection module 24 VDC | V 1.2.0 | pdf<br>2.2 MB | Download |
|----------------------------------------------------|---------|---------------|----------|

|                                             |  |     |          |
|---------------------------------------------|--|-----|----------|
| System Manual Series 750/753<br>Online HTML |  | URL | Download |
|---------------------------------------------|--|-----|----------|

**Bid Text**

|                        |             |               |          |
|------------------------|-------------|---------------|----------|
| 753-603<br>X81 - Datei | 2019 Feb 19 | xml<br>4.6 kB | Download |
|------------------------|-------------|---------------|----------|

|                        |            |                |          |
|------------------------|------------|----------------|----------|
| 753-603<br>doc - Datei | 2017 Oct 6 | doc<br>27.6 kB | Download |
|------------------------|------------|----------------|----------|

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Instruction Leaflet

|                                                                |             |                 |          |
|----------------------------------------------------------------|-------------|-----------------|----------|
| CCC Ex (Additional information)<br>WAGO-I/O-SYSTEM *750-****/* | 2023 Apr 26 | pdf<br>163.6 kB | Download |
|----------------------------------------------------------------|-------------|-----------------|----------|

## System Description

|                                                         |  |                 |          |
|---------------------------------------------------------|--|-----------------|----------|
| Overview on WAGO-I/O-SYSTEM 750 approvals               |  | pdf<br>223.5 kB | Download |
| 750/753 Series I/O-System – General Product Information |  | pdf<br>976.2 kB | Download |

## Additional Information

|                                                                                     |                        |               |          |
|-------------------------------------------------------------------------------------|------------------------|---------------|----------|
| Disposal and Recycling<br>Electrical and electronic equipment, Batteries, Packaging | V 1.1.0<br>2022 Aug 18 | pdf<br>2.2 MB | Download |
|-------------------------------------------------------------------------------------|------------------------|---------------|----------|

## CAD/CAE-Data

### CAD data

|                      |     |          |
|----------------------|-----|----------|
| 2D/3D Models 753-603 | URL | Download |
|----------------------|-----|----------|

### CAE data

|                           |     |          |
|---------------------------|-----|----------|
| WSCAD Universe 753-603    | URL | Download |
| ZUKEN Portal 753-603      | URL | Download |
| EPLAN Data Portal 753-603 | URL | Download |

## Asset Administration Shell

|                                    |     |          |
|------------------------------------|-----|----------|
| Asset Administration Shell 753-603 | URL | Download |
|------------------------------------|-----|----------|

## Environmental Product Compliance

### Compliance Search

|                                                                                |     |          |
|--------------------------------------------------------------------------------|-----|----------|
| Environmental Product Compliance 753-603<br>Potential Distribution; 8-way 24 V | URL | Download |
|--------------------------------------------------------------------------------|-----|----------|

Subject to changes. Please also observe the further product documentation!



## Installation Notes

## Product family

**WAGO I/O System 750/753**

Show all products from the family

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.