



Data sheet | Item number: 756-3104/040-200

Power cable; M12A plug; angled; 4-pole; Length: 20 m

www.wago.com/756-3104/040-200



Pin 1 ... 4: 0.75 mm²

1	■	brown	_____
2	■	white	_____
3	■	blue	_____
4	■	black	_____

Item description

Short description:

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



- PUR, halogen-free
- UL / CSA
- Suitable for drag chains
- Silicon- and CFC-free
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Data

Technical data

Connection type	M12 plug - free end
Pole number	4
Cable connection direction to mating direction	90 °
Connector interface coding (cable/adaptor) 1 1	A-coded
Cable length	20 m
PLC manufacturer	WAGO
Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Insulation resistance	>10 ⁹ Ω
Conductor resistance	≤ 26 Ω/km

Mechanical Data

Bending radius	10 x cable diameter (min.) for flexible application
Bending cycles	4 Mio.
Drag chain capability	yes
Sheathed cable diameter	6 ... 6.4 mm
Type code	Lif9YH-11YH 4x0.75 mm ²
Conductor configuration	Bare copper wire (40 x 0.15 mm)
Conductor insulation	PP9Y (halogen-free)
Housing material	TPU/TPU, black (~ RAL 9005)
Tightening torque	1 Nm
Weight	10 g

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Environmental requirements

Ambient (operating) temperature (dynamic)	-30 ... +80 °C
Ambient (operating) temperature (static)	-30 ... +80 °C
Protection type	IP67
Pollution degree	3/2 per IEC 60664-1

Commercial data

eCl@ss 10.0	27-06-18-01
eCl@ss 9.0	27-06-18-01
ETIM 8.0	EC001855
ETIM 7.0	EC003249
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4045454772369
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	b7018b4a-e362-4c96-965f-0ba6d79238f8
SCIP notification number (Belgium)	5be6c404-3501-43ac-b241-e9b1b2a75250
SCIP notification number (Bulgaria)	c34b3ec1-cd49-4def-95af-e640cc3b2daa
SCIP notification number (Czech Republic)	eb01db87-6e57-4c17-a212-bf23d36021df
SCIP notification number (Denmark)	1f80dac4-cf77-40cf-8f43-4d7a3bce408a
SCIP notification number (Finland)	60959d88-38be-438d-9097-ab8973c0cf34
SCIP notification number (France)	83792182-a269-4df1-828a-692ce421c5a3
SCIP notification number (Germany)	a07dfbc1-475b-4596-964b-15a08fdf803b
SCIP notification number (Hungary)	4451aa7a-0e0b-406d-b903-0f5284e4094d
SCIP notification number (Italy)	c8389565-041c-4535-8615-2f0b34448d90
SCIP notification number (Netherlands)	775ae2fd-9481-4a47-9a6d-7b46141af740
SCIP notification number (Poland)	b86db83c-41a4-418f-9966-7471fd6b9574
SCIP notification number (Romania)	8993a8d4-f42d-48ac-9acb-6ba7121abf9e
SCIP notification number (Sweden)	9cd837d9-32fd-4f29-b456-0b22ec032c7f

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

System Description

I/O-SYSTEM – SPEEDWAY, General Product Information	pdf 1.1 MB	Download
--	---------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-3104/040-200	URL	Download
WSCAD Universe 756-3104/040-200	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-3104/040-200 Power cable; M12A plug; angled; 4-pole; Length: 20 m	URL	Download
---	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.