



Data sheet | Item number: 756-5202/030-010

Sensor/Actuator cable; M8 socket; straight; M8 plug; angled; 3-pole; Length: 1 m


www.wago.com/756-5202/030-010



 Picture differs from the item.



Pin 1 ... 4: 0.25 mm²



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Data

Technical data

General information

Operating voltage	60 VAC/DC
Operating current	4 A
Rated surge voltage	1.5 kV
Insulation resistance	$> 10^9 \Omega$
Contact resistance	10 m Ω
Conductor resistance	$\leq 60 \Omega/\text{km}$
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Drag chain compatible

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	1 m
Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	3.9 ... 4.3 mm

Connector

Connection type	M8 socket - M8 plug
-----------------	---------------------

Subject to changes. Please also observe the further product documentation!



Pole number	3
Cable connection direction to mating direction	0 °
Cable connection direction to mating direction (2)	90 °
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	0.6 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918974578
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	6a4774c4-8f01-4961-98d8-f0974fed2fba
SCIP notification number (Belgium)	5ca78889-9477-407e-ad4a-4fc337775556
SCIP notification number (Bulgaria)	d01ec0bb-7ad8-4f43-9697-b9f2f0cd8c6b
SCIP notification number (Czech Republic)	8d274a1e-b8b0-4b88-9c9d-b34c85f451b7
SCIP notification number (Denmark)	a4dc4e43-174e-4e93-bc26-65a5e2bc82fa
SCIP notification number (Finland)	177022d2-63cc-4ac0-8824-e97f19258c16
SCIP notification number (France)	73f56c6d-0765-4798-8b35-4f8a954576b7
SCIP notification number (Germany)	aafe55cc-cf1a-4531-babf-bee0a6d19e22
SCIP notification number (Hungary)	ebc63f9a-fb18-4aaa-9ddc-82586dd4750b
SCIP notification number (Italy)	1b6c034a-0140-454c-b565-5a8bba23173d
SCIP notification number (Netherlands)	d42e7c41-6688-4a9a-a33e-0727fd18fa48
SCIP notification number (Poland)	de54d67a-3329-47b5-908e-68bc732456c1
SCIP notification number (Romania)	52bf8529-0e89-427b-bf3f-17fe9e98e519
SCIP notification number (Sweden)	67f199b4-4100-4ecf-af61-16965cb0ed74

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Commercial data

eCl@ss 9.0

ETIM 8.0

ETIM 7.0

Customs tariff number

Downloads

Documentation

Bid Text

756-5202/030-010	2019 Feb 19	xml	Download
X81 - Datei		3.3 kB	

756-5202/030-010	2017 Sep 20	doc	Download
doc - Datei		26.1 kB	

System Description

IP67 Cables and Pluggable Connectors		pdf	Download
		130.8 kB	

CAD/CAE-Data

CAE data

WSCAD Universe 756-5202/030-010	URL	Download
---------------------------------	-----	----------

WSCAD Universe 756-5202/030-010	URL	Download
---------------------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5202/030-010	URL	Download
Sensor/Actuator cable; M8 socket; straight; M8 plug; angled; 3-pole; Length: 1 m		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.