



Part Number : [349511641](#)

Product Description : MX150 90° Backshell Adapter for Female Sealed Connector Assembly, 16 or 20 Circuit, without Rib

Series Number : [34951](#)

Status : Active

Product Category : [Connector Housings](#)



Documents & Resources

Drawings

[Drawing 349511641_sd.pdf](#)

[Packaging Design Drawing 349509000-000.pdf](#)

3D Models and Design Files

[3D Model 349511641_stp.zip](#)

Specifications

[Application Specification AS-34951-001-001.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|------------------------------------------------|
| GADSL/IMDS | Compliant |
| China RoHS | Not Relevant |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant per EU 2015/863 |

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|-------------------------------------------------------------------------------------------------|
| Status | Active |
| Category | Connector Housings |
| Series | 34951 |
| Description | MX150 90° Backshell Adapter for Female Sealed Connector Assembly, 16 or 20 Circuit, without Rib |
| Application | Power, Wire-to-Wire |
| Comments | Without Rib |
| Product Family | MX150 Sealed and Unsealed Connector System |
| Product Name | MX150 |
| UPC | 191128782913 |

Physical

| | |
|-------------------------------|----------------|
| Circuits (maximum) | 16, 20 |
| Color - Resin | Black |
| Gender | N/A |
| Glow-Wire Capable | No |
| Lock to Mating Part | Yes |
| Material - Resin | Nylon |
| Net Weight | 6.900/g |
| Number of Rows | 0 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | N/A |
| Polarized to Mating Part | Yes |
| Stackable | No |
| Temperature Range - Operating | -40° to +125°C |

Use with Part(s)

| Description | Part Number |
|----------------------------------------------------------|--------------|
| MX150 Mat-Sealed Dual Row Female Connector Assemblies | <u>33472</u> |
