




Part Number : 431805002

Product Description : 7.50mm Pitch, Flat Blade Plug Housing, Free Hanging, Single Row, 2 Circuits, Nylon PA6, UL94V-0, Black, Glow-Wire Capable

Series Number : 43180

Status : Active

Product Category : Connector Housings



Documents & Resources

Drawings

[Drawing 431805002_sd.pdf](#)

3D Models and Design Files

[3D Model 431805002_stp.zip](#)

Specifications

[Packaging Specification PK-43180-001-001.pdf](#)

[Test Summary TS-5556-002-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	43180
Description	7.50mm Pitch, Flat Blade Plug Housing, Free Hanging, Single Row, 2 Circuits, Nylon PA6, UL94V-0, Black, Glow-Wire Capable
Application	Power, Wire-to-Wire
Comments	This Molex product is manufactured from material that has the following ratings, tested by independent agencies: a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12 and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options.
Product Name	Flat Blade
UPC	800756824802

Agency

UL	E29179
----	--------

Physical

Breakaway	No
Circuits (maximum)	2
Color - Resin	Black
Flammability	94V-0
Gender	Plug
Glow-Wire Capable	Yes
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	3.401/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	7.49mm
Pitch - Termination Interface	7.49mm
Polarized to Mating Part	Yes
Ports	1
Stackable	No
Temperature Range - Operating	-40° to +75°C

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
Flat Blade Appliance Single Row Receptacle Housings	<u>43335</u>

Use with Part(s)

Description	Part Number
Flat Blade Appliance Single Row Receptacle Housings	<u>43335</u>

This document was generated on Jan 24, 2024